


MHO+ Series

14 pin DIP, 5.0 Volt, HCMOS/TTL, Clock Oscillator



Features:

- Standard 14 DIP Package
- RoHS Compliant Version Available (-R)
- Tristate Option
- Wide Operating Temperature Range



Pin Connections

PIN	FUNCTION
1	N/C or Tristate
7	Circuit/Case Ground
8	Output
14	+Vdd

Available Symmetry

FREQUENCY RANGE	STD.	OPTIONS
0.732 kHz to 50 MHz	A	B, C, D
50.001 to 60 MHz	A	B, C
60.001 to 67 MHz	A	C
67.001 to 80 MHz	F,G	C

Ordering Information

Product Series	MHO+	1	3	F	A	D	-R	00.0000 MHz
Temperature Range								
1: 0°C to +70°C								
2: -40°C to +85°C								
3: -55°C to +105°C								
4: -55°C to +125°C								
5: -10°C to +85°C								
6: -20°C to +70°C								
7: 0°C to +85°C								
Stability								
1: ±1000 ppm								
2: ±500 ppm								
3: ±100 ppm								
4: ±50 ppm								
5: ±35 ppm								
6: ±25 ppm								
7: ±0/-200 ppm								
*8: ±20 ppm								
Output Type								
F: Fixed								
T: Tristate (1.000 to 80.000 MHz)								
Symmetry/Logic Compatibility (See Table Below)								
A: 40/60 HCMOS/TTL								
B: 45/55 TTL								
C: 45/55 HCMOS								
D: 45/55 HCMOS/TTL								
F: 40/60 TTL								
G: 40/60 HCMOS								
Package/Lead Configurations								
D: DIP; Nickel Header								
G: Gull Wing; Nickel Header								
RoHS Compliance								
Blank: non-RoHS compliant part								
-R: RoHS compliant part								
Frequency (customer specified)								

*Contact factory for availability
M2014Sxxx - Contact factory for datasheet.

PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
Frequency Range	F	.732 kHz		80	MHz	See Note 1
Operating Temperature	T _A	(See ordering information)				
Storage Temperature	T _S	-55		+125	°C	
Frequency Stability	ΔF/F	(See ordering information)				
Aging						
1st Year			±3		ppm	
Thereafter (per year)			±2		ppm	
Input Voltage	V _{dd}	4.5	5.0	5.5	V	
Input Current	I _{dd}			15 25 60	mA mA mA	.732 kHz to 2.999 MHz 3.000 to 25.999 MHz 26.000 to 80.000 MHz
Output Type						HCMOS/TTL
Load						See Note 2 5 TTL or 50 pF 10 TTL or 50 pF 10 TTL or 15 pF .732 kHz to 2.999 MHz 3.000 to 25.999 MHz 26.000 to 80.000 MHz
Symmetry (Duty Cycle)						See Note 3
Logic "1" Level	V _{oh}	90% V _{dd} V _{dd} -0.5			V V	HCMOS Load TTL Load
Logic "0" Level	V _{ol}			10% V _{dd} 0.5	V V	HCMOS Load TTL Load
Output Current				±8 ±16	mA mA	.732 kHz to 2.999 MHz 3.000 to 80.000 MHz
Rise/Fall Time	T _r /T _f			20 10	ns ns	See Note 4 .732 kHz to 2.999 MHz 3.000 to 80.000 MHz
Tristate Function		Input Logic "1" or floating: output active Input Logic "0": output to high-Z				
Start up Time				10	ms	
Random Jitter	R _j		5	12	ps RMS	1-Sigma
Mechanical Shock		MIL-STD-202, Method 213, C (100 g's)				
Vibration		MIL-STD-202, Method 201 & 204 (10 g's from 10-2000 Hz)				
Thermal Cycle		MIL-STD-883, Method 1010, B (-55°C to +125°C, 15 min dwell, 10 cycles)				
Hermeticity		MIL-STD-202, Method 112				
Solderability		Per EIAJ-STD-002				
Max Wave Soldering Conditions		+260°C for 10 seconds				

1. Contact the factory for availability of higher frequencies.
2. TTL load - see Load Circuit Diagram #1. HCMOS load - see Load Circuit Diagram #2.
3. Symmetry is measured at 1.4 V with TTL load and at 50% V_{dd} with HCMOS load.
4. Rise/fall times are frequency dependent and measured between 0.4 V and 2.4 V with TTL load, and between 10% V_{dd} and 90% V_{dd} with HCMOS Load.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

Revision: 9-23-10