

Note: This datasheet may be out of date.

Please download the latest datasheet of BL02RN2R3J2# from the official website of Murata Manufacturing Co.,

Ltd. https://www.murata.com/en-us/products/productdetail?partno=BL02RN2R3J2%23

BL02RN2R3J2#

"#" indicates a package specification code.








< List of part numbers with package codes >

BL02RN2R3J2B



Appearance & Shape





ø0.65



BL01/02/03 series are ferrite beads with lead wires to produce a high frequency loss for suppression of noise. Simple construction and easy-to-use, effective for low impedance circuits such as power supplies and grounds. Effective also for preventing overshoot and undershoot of digital signal in clocks or the like, and suppressing the higher harmonic wave. Suitable for prevention of abnormal oscillation at high frequency amplifying circuit.



Applications

Other Usage

For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2020/01/24



Note: This datasheet may be out of date $\underline{ Please \ download \ the \ latest \ datasheet \ of \ BL02RN2R3J2\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing \ Co.,}$

https://www.murata.com/en-us/products/productdetail?partno=BL02RN2R3J2%23

BL02RN2R3J2#

"#" indicates a package specification code.



Shape	Lead
Length	9.0mm
Length Tolerance	max.
Width	3.4mm
Width Tolerance	±0.2mm
Thickness	12.0mm
Thickness Tolerance	max.
Rated Current (at 85°C)	7A
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.57g
Number of Circuit	1

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2020/01/24

Note: This datasheet may be out of date.


 $\underline{ Please \ download \ the \ latest \ datasheet \ of \ BL02RN2R3J2\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing \ Co.,}$


https://www.murata.com/en-us/products/productdetail?partno=BL02RN2R3J2%23

BL02RN2R3J2#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

