



Note: This datasheet may be out of date

Please download the latest datasheet of CFUKF455KE1X-R0 from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=CFUKF455KE1X-R0

CFUKF455KE1X-R0










Appearance & Shape







Features

The CFUKF series is comprised of small, high-performance, thin (4.0mm) filters consisting of 4 ceramic elements. The filters exhibit an extremely flat GDT characteristic. The filters are recommended for digital communication applications and are perfect in hand-held cellular phones, etc.

Features

- 1. The filters are mountable by automatic placers.
- 2. The filters can be reflow soldered and withstand washing.
- 3. They are slim, at only 4.0mm maximum thickness, and have a small mounting area (7.5x6.0mm) enabling flexible PCB design.
- 4. The bandwidth ranges from Ato E.
- 5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)



Other Usage

Communication Equipment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-R0	180mm Embossed Tape	450

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2020/01/24

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=CFUKF455KE1X-R0

CFUKF455KE1X-R0



Operating Temperature Range	-20°C to 80°C	
Shape	SMD	
Elements	4	
Center Frequency	455.0kHz	
Center Frequency Tolerance	±1kHz	
Nominal Center Value	No	
6dB Bandwidth	fn±7.5kHzmin.	
Stop Bandwidth	20.0kHz	
Area of Stop Bandwidth	[within 40dB]	
Stop Band Attenuation	23dB[within fn±100kHz]	
Insertion Loss	8.0dB[at minimum loss point]	
Ripple	1.0dB[within fn±5kHz]	
GDT Deviation	20.0µs[within fn±5kHz]	
Input/Output Impedance	1500Ω	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2020/01/24


Note: This datasheet may be out of date $\underline{\textbf{Please download the latest datasheet of CFUKF455KE1X-R0 from the official website of Murata Manufacturing}$


Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=CFUKF455KE1X-R0

CFUKF455KE1X-R0








Frequency Characteristics

Spurious Response



Rg+R1=R2=Input/Output Impedance

Measurement Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2020/01/24