

GQM1875C2E180JB12#

" # " indicates a package specification code.

Recommended

Flow OK


Reflow OK

Complies with RoHS

HIQ

< List of part numbers with package codes >
GQM1875C2E180JB12D , GQM1875C2E180JB12B

Shape



L size	1.6 ± 0.15mm
W size	0.8 ± 0.15mm
T size	0.7 ± 0.1mm
External terminal width e	0.2 to 0.5mm
Distance between external terminals g (Min.)	0.5mm
Size code in mm(inch)	1608 (0603)

References

Packaging	Specifications	Minimum quantity
D	Paper tape (φ 180mm)	4000
B	Packing in bulk	1000

Mass (typ.)	
1 piece	6.3mg
Reel (φ 180mm)	144g


Specifications

Capacitance	18pF ± 5%
Rated voltage	250Vdc
Temperature characteristics (complied standard)	COG(EIA)
Temperature coefficient	0 ± 30ppm/
Temperature range of temperature characteristics	25 to 125
Operating temperature range	-55 to 125


 Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.


▪ Frequency characteristics (ESR, Impedance)




▪ S parameter (Smith chart S11)




▪ DC bias characteristics



▪ AC voltage characteristics



▪ Capacitance - temperature characteristics



▪ Calorific property by ripple current

