Note: This datasheet may be out of date Please download the latest datasheet of LQH44NN1R5M03# from the official website of Murata Manufacturing

LQH44NN1R5M03#

"#" indicates a package specification code.

Size Code 4040 (1515) in mm (in inch), General use
















< List of part numbers with package codes > LQH44NN1R5M03K LQH44NN1R5M03L



Appearance & Shape







References

| Packaging | Specifications | Minimum Order Quantity |
|-----------|------------------|---------------------------|
| К | 330Embossed Tape | 1500 |
| L | 180Embossed Tape | 250 |

| Mass (typ.) | |
|-------------|-------|
| 1 piece | 0.26g |



When rated current is applied to the products, inductance will be within ±30% of initial inductance value. When rated current is applied to the products, the temperature rise caused by self-generated heat shall be limited to 40°C max.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of LQH44NN1R5M03# from the official website of Murata Manufacturing Co., Ltd.

LQH44NN1R5M03#

"#" indicates a package specification code.



| L size | 4.0±0.2mm |
|--|----------------|
| W size | 4.0±0.2mm |
| T size | 4.3±0.2mm |
| Size code inch (mm) | 1515 (4040) |
| Inductance | 1.5µH±20% |
| Inductance Test Frequency | 1kHz |
| Rated current (Itemp) (Based on Temperature rise) | 3.20A |
| Max. of DC resistance | 0.0208Ω |
| Operating Temperature Range (Self-temperature rise is included) | -40°C to 125°C |
| Class of magnetic shield | No Shield |
| Self resonance frequency (min.) | 70MHz |
| Operating Temperature Range(Self- temperature rise is not included) | -40°C to 85°C |
| DC Resistance Intermediate Values | 0.016Ω±30% |
| Series | LQH44NN_03 |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date. Please download the latest datasheet of LQH44NN1R5M03# from the official website of Murata Manufacturing Co., Ltd.

LQH44NN1R5M03#

"#" indicates a package specification code.





Impedance - Current Characteristics

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

