



Deutsche Version

- [Home](#)
- [About Us](#)
- Products**
 - Audio**
 - [Video](#)
 - [Lighting](#)
 - [Data Connectors](#)
 - [Industrial](#)

- [Support](#)
- [News](#)
- [Sitemap](#)

Search

PRODUCTS ONLY

Search

© Neutrik® AG
 All rights reserved
[Legal Notices](#)



NC5FBH



Product

Connector Type	XLR
Gender	female

Electrical

Capacitance between contacts	≤ 7 pF
Contact resistance	≤ 5 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 2 GΩ (initial)
Insulation resistance	> 1 GΩ (after damp heat test)
Rated current per contact	3 A
Rated voltage	50 V

Grounding options: Separate ground contact connected to mating connector shell and front panel, no connection to Pin 1

Mechanical

Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiring	Horizontal PCB mount
Locking device	latch lock
Mounting direction	rear
Chassis shape	B
Mounting	A-Screw

Material

Contact plating	0.2 μm AuCo over 2 μm NiP15 (Tribor®)
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	Steel Ck67
Ring	Zinc diecast (ZnAl4Cu1)
Flange	Metal

Environmental

Flammability	UL 94 HB
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C