

Mini relay

G6A-274P DC5

No Image Available

Image

Standard type, Crossbar / Twin, Terminal for printed circuit board, DC30V 2A (Resistive load), AC125V 0.5A (Resistive load), Output 2c (2A 30V)

Coil rating	DC5V 40mA
Contact configuration	2c
Contact mechanism	Crossbar Twin
Contact material	Au alloy + Ag
Contact rated load	AC125V 0.5A (Resistive load) AC125V 0.3A (Inductive load (cos ϕ = 0.4)) DC30V 2A (Resistive load) DC30V 1A (Inductive load (L / R = 7ms))
Terminal structure	Printed circuit board terminal

Rating / performance

Information update: 2019/02/26

Rated

Product classification		Standard type single stable relay monostable
Protective structure		Plastic seal type
Terminal structure		Printed circuit board terminal
coil	Coil rating	DC5V 40mA
	Coil resistance	125 Ω
	Operating voltage (set voltage)	70% or less
	Return voltage (reset voltage)	More than 10
	Maximum allowable voltage	200% (23 ° C)
	power consumption	About 200mW
contact	Rated load	AC125V 0.5A (Resistive load) AC125V 0.3A (Inductive load (cos ϕ = 0.4)) DC30V 2A (Resistive load) DC30V 1A (Inductive load (L / R = 7ms))
	Maximum value of contact voltage	AC250V DC220V
	Maximum value of contact current	AC: 2A (Resistive load) AC: 1A (Inductive load (cos ϕ = 0.4)) DC: 2A (Resistive load) DC: 1A (Inductive load (L / R = 7ms))
	Contact configuration	2c
	Contact mechanism	Crossbar Twin
	Contact material	Au alloy + Ag

Performance

Contact resistance	50mΩ or less (DC1V 10mA voltage drop method)
Operating time	5 ms or less
Recovery time	3 ms or less
Insulation resistance	Between coil and contact: 1000 MΩ or more (DC500 V insulation resistance meter) Between different pole contacts: 1000 MΩ or more (DC 500 V insulation resistance meter) Between same pole contacts: 1000 MΩ or more (DC 500 V insulation resistance meter)
Withstand voltage	Between coil and contact: AC1000V 50 / 60Hz 1min Between different pole contacts: AC1000V 50 / 60Hz 1min Between same pole contacts: AC1000V 50 / 60Hz 1min
Vibration resistant (durable)	10 to 55 to 10 Hz Single amplitude 2.5 mm (Double amplitude 5 mm)
Vibration resistance (malfunction)	10 to 55 to 10 Hz Single amplitude 1.65 mm (Double amplitude 3.3 mm)
Impact resistant (durable)	1000 m / s ** 2
Shock resistance (malfunction)	500 m / s ** 2
durability	Mechanical: 100 million times or more (switching frequency 36,000 times / h) Electrical: 500,000 times or more (rated load, switching frequency 1,800 times / h)
failure rate	DC10mV 10 μ A (P level, reference value) (switching frequency 60 times / min)
Operating temperature limit	-40 to 70 ° C (with no icing or condensation)
Operating humidity range	5 to 85% RH (with no icing or condensation)
mass	Approximately 3.5 g

Information update: 2019/02/26

Page top

Notice / Latest Information

product

Technical Guide

Service support

Semina

solution

Manufacturing site innovation

Event

publication

Field data utilization service

i-BELT

Products Supporting i-Automation!

Panel Solution (Control Panel)

Sensor

switch

Safety

relay

Control

FA system equipment

Motion / drive

Robotics

Energy saving support / Environmental measures equipment

Power supply / peripheral equipment etc

Product FAQ

Technical explanation

FA glossary

Download center

catalog

manual

2D CAD

3D CAD

Electrical control CAD

software

Robotics support

Japanese Counseling Desk

Japan Desk

World Regional Service Information

Choose from practice set

Choose from learning)

Choose from

Introductory employees

Designer In Course

Introductory maintainer

online store

OMRON Corporation

help

site map

Related Links

About the handling of personal information

Terms of use