

# Single-Channel: 6N137, HCPL2601, HCPL2611 Dual-Channel: HCPL2630, HCPL2631 High Speed 10MBit/s Logic Gate Optocouplers

## Features

- Very high speed – 10 MBit/s
- Superior CMR – 10 kV/μs
- Double working voltage-480V
- Fan-out of 8 over -40°C to +85°C
- Logic gate output
- Strobable output
- Wired OR-open collector
- U.L. recognized (File # E90700)

## Applications


- Ground loop elimination
- LSTTL to TTL, LSTTL or 5-volt CMOS
- Line receiver, data transmission
- Data multiplexing
- Switching power supplies
- Pulse transformer replacement
- Computer-peripheral interface

## Description

The 6N137, HCPL2601, HCPL2611 single-channel and HCPL2630, HCPL2631 dual-channel optocouplers consist of a 850 nm AlGaAs LED, optically coupled to a very high speed integrated photo-detector logic gate with a strobable output. This output features an open collector, thereby permitting wired OR outputs. The coupled parameters are guaranteed over the temperature range of -40°C to +85°C. A maximum input signal of 5mA will provide a minimum output sink current of 13mA (fan out of 8).


An internal noise shield provides superior common mode rejection of typically 10kV/μs. The HCPL2601 and HCPL2631 has a minimum CMR of 5kV/μs. The HCPL2611 has a minimum CMR of 10kV/μs.

## Schematics



A 0.1μF bypass capacitor must be connected between pins 8 and 5<sup>(1)</sup>.

## Package Outlines



## Truth Table (Positive Logic)

| Input | Enable | Output |
|-------|--------|--------|
| H     | H      | L      |
| L     | H      | H      |
| H     | L      | H      |
| L     | L      | H      |
| H     | NC     | L      |
| L     | NC     | H      |

**Absolute Maximum Ratings** ( $T_A = 25^\circ\text{C}$  unless otherwise specified)

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol                            | Parameter                                                             |                             | Value          | Units |
|-----------------------------------|-----------------------------------------------------------------------|-----------------------------|----------------|-------|
| T <sub>STG</sub>                  | Storage Temperature                                                   |                             | -55 to +125    | °C    |
| T <sub>OPR</sub>                  | Operating Temperature                                                 |                             | -40 to +85     | °C    |
| T <sub>SOL</sub>                  | Lead Solder Temperature (for wave soldering only)*                    |                             | 260 for 10 sec | °C    |
| EMITTER                           |                                                                       |                             |                |       |
| I <sub>F</sub>                    | DC/Average Forward                                                    | Single Channel              | 50             | mA    |
|                                   | Input Current                                                         | Dual Channel (Each Channel) | 30             |       |
| V <sub>E</sub>                    | Enable Input Voltage Not to Exceed V <sub>CC</sub> by more than 500mV | Single Channel              | 5.5            | V     |
| V <sub>R</sub>                    | Reverse Input Voltage                                                 | Each Channel                | 5.0            | V     |
| P <sub>I</sub>                    | Power Dissipation                                                     | Single Channel              | 100            | mW    |
|                                   |                                                                       | Dual Channel (Each Channel) | 45             |       |
| DETECTOR                          |                                                                       |                             |                |       |
| V <sub>CC</sub><br>(1 minute max) | Supply Voltage                                                        |                             | 7.0            | V     |
| I <sub>O</sub>                    | Output Current                                                        | Single Channel              | 50             | mA    |
|                                   |                                                                       | Dual Channel (Each Channel) | 50             |       |
| V <sub>O</sub>                    | Output Voltage                                                        | Each Channel                | 7.0            | V     |
| P <sub>O</sub>                    | Collector Output                                                      | Single Channel              | 85             | mW    |
|                                   | Power Dissipation                                                     | Dual Channel (Each Channel) | 60             |       |

\*For peak soldering reflow, please refer to the Reflow Profile on page 11.

**Recommended Operating Conditions**

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to absolute maximum ratings.

| Symbol   | Parameter                  | Min. | Max.     | Units            |
|----------|----------------------------|------|----------|------------------|
| $I_{FL}$ | Input Current, Low Level   | 0    | 250      | $\mu\text{A}$    |
| $I_{FH}$ | Input Current, High Level  | *6.3 | 15       | mA               |
| $V_{CC}$ | Supply Voltage, Output     | 4.5  | 5.5      | V                |
| $V_{EL}$ | Enable Voltage, Low Level  | 0    | 0.8      | V                |
| $V_{EH}$ | Enable Voltage, High Level | 2.0  | $V_{CC}$ | V                |
| $T_A$    | Low Level Supply Current   | -40  | +85      | $^\circ\text{C}$ |
| N        | Fan Out (TTL load)         |      | 8        |                  |

\*6.3mA is a guard banded value which allows for at least 20% CTR degradation. Initial input current threshold value is 5.0mA or less.

**Electrical Characteristics** ( $T_A = 0$  to  $70^\circ\text{C}$  unless otherwise specified)**Individual Component Characteristics**

| Symbol                    | Parameter                           | Test Conditions                                                      | Min.                                                                   | Typ.*   | Max.        | Unit                 |
|---------------------------|-------------------------------------|----------------------------------------------------------------------|------------------------------------------------------------------------|---------|-------------|----------------------|
| <b>EMITTER</b>            |                                     |                                                                      |                                                                        |         |             |                      |
| $V_F$                     | Input Forward Voltage               | $I_F = 10\text{mA}$<br>$T_A = 25^\circ\text{C}$                      |                                                                        | 1.4     | 1.8<br>1.75 | V                    |
| $B_{VR}$                  | Input Reverse Breakdown Voltage     | $I_R = 10\mu\text{A}$                                                | 5.0                                                                    |         |             | V                    |
| $C_{IN}$                  | Input Capacitance                   | $V_F = 0$ , $f = 1\text{MHz}$                                        |                                                                        | 60      |             | pF                   |
| $\Delta V_F / \Delta T_A$ | Input Diode Temperature Coefficient | $I_F = 10\text{mA}$                                                  |                                                                        | -1.4    |             | mV/ $^\circ\text{C}$ |
| <b>DETECTOR</b>           |                                     |                                                                      |                                                                        |         |             |                      |
| $I_{CCH}$                 | High Level Supply Current           | $V_{CC} = 5.5\text{V}$ , $I_F = 0\text{mA}$ ,<br>$V_E = 0.5\text{V}$ | Single Channel<br>Dual Channel                                         | 7<br>10 | 10<br>15    | mA                   |
| $I_{CCL}$                 | Low Level Supply Current            | Single Channel<br>Dual Channel                                       | $V_{CC} = 5.5\text{V}$ ,<br>$I_F = 10\text{mA}$<br>$V_E = 0.5\text{V}$ | 9<br>14 | 13<br>21    | mA                   |
| $I_{EL}$                  | Low Level Enable Current            | $V_{CC} = 5.5\text{V}$ , $V_E = 0.5\text{V}$                         |                                                                        | -0.8    | -1.6        | mA                   |
| $I_{EH}$                  | High Level Enable Current           | $V_{CC} = 5.5\text{V}$ , $V_E = 2.0\text{V}$                         |                                                                        | -0.6    | -1.6        | mA                   |
| $V_{EH}$                  | High Level Enable Voltage           | $V_{CC} = 5.5\text{V}$ , $I_F = 10\text{mA}$                         | 2.0                                                                    |         |             | V                    |
| $V_{EL}$                  | Low Level Enable Voltage            | $V_{CC} = 5.5\text{V}$ , $I_F = 10\text{mA}^{(3)}$                   |                                                                        |         | 0.8         | V                    |

**Switching Characteristics** ( $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$ ,  $V_{CC} = 5\text{V}$ ,  $I_F = 7.5\text{mA}$  unless otherwise specified)

| Symbol                | AC Characteristics                                    | Test Conditions                                                                                                                                                                | Min.                                              | Typ.*                      | Max.      | Unit                                 |
|-----------------------|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|----------------------------|-----------|--------------------------------------|
| $T_{PLH}$             | Propagation Delay Time to Output HIGH Level           | $R_L = 350\Omega$ , $C_L = 15\text{pF}^{(4)}$ (Fig. 12)<br>$T_A = 25^\circ\text{C}$                                                                                            | 20                                                | 45                         | 75<br>100 | ns                                   |
| $T_{PHL}$             | Propagation Delay Time to Output LOW Level            | $T_A = 25^\circ\text{C}^{(5)}$<br>$R_L = 350\Omega$ , $C_L = 15\text{pF}$ (Fig. 12)                                                                                            | 25                                                | 45                         | 75<br>100 | ns                                   |
| $ T_{PHL} - T_{PLH} $ | Pulse Width Distortion                                | $(R_L = 350\Omega, C_L = 15\text{pF})$ (Fig. 12)                                                                                                                               |                                                   | 3                          | 35        | ns                                   |
| $t_r$                 | Output Rise Time (10–90%)                             | $R_L = 350\Omega$ , $C_L = 15\text{pF}^{(6)}$ (Fig. 12)                                                                                                                        |                                                   | 50                         |           | ns                                   |
| $t_f$                 | Output Rise Time (90–10%)                             | $R_L = 350\Omega$ , $C_L = 15\text{pF}^{(7)}$ (Fig. 12)                                                                                                                        |                                                   | 12                         |           | ns                                   |
| $t_{ELH}$             | Enable Propagation Delay Time to Output HIGH Level    | $I_F = 7.5\text{mA}$ , $V_{EH} = 3.5\text{V}$ , $R_L = 350\Omega$ , $C_L = 15\text{pF}^{(8)}$ (Fig. 13)                                                                        |                                                   | 20                         |           | ns                                   |
| $t_{EHL}$             | Enable Propagation Delay Time to Output LOW Level     | $I_F = 7.5\text{mA}$ , $V_{EH} = 3.5\text{V}$ , $R_L = 350\Omega$ , $C_L = 15\text{pF}^{(9)}$ (Fig. 13)                                                                        |                                                   | 20                         |           | ns                                   |
| $ ICM_H $             | Common Mode Transient Immunity (at Output HIGH Level) | $T_A = 25^\circ\text{C}$ , $ IV_{CM}  = 50\text{V}$ (Peak), $I_F = 0\text{mA}$ ,<br>$V_{OH}$ (Min.) = 2.0V,<br>$R_L = 350\Omega^{(10)}$ (Fig. 14)<br>$ IV_{CM}  = 400\text{V}$ | 6N137, HCPL2630<br>HCPL2601, HCPL2631             | 10,000<br>10,000           |           | V/ $\mu\text{s}$<br>V/ $\mu\text{s}$ |
| $ ICM_L $             | Common Mode Transient Immunity (at Output LOW Level)  | $R_L = 350\Omega$ , $I_F = 7.5\text{mA}$ ,<br>$V_{OL}$ (Max.) = 0.8V,<br>$T_A = 25^\circ\text{C}^{(11)}$ (Fig. 14)<br>$ IV_{CM}  = 400\text{V}$                                | 6N137, HCPL2630<br>HCPL2601, HCPL2631<br>HCPL2611 | 10,000<br>10,000<br>10,000 |           | V/ $\mu\text{s}$                     |

**Electrical Characteristics** (Continued)**Transfer Characteristics** ( $T_A = -40$  to  $+85^\circ\text{C}$  unless otherwise specified)

| Symbol   | DC Characteristics        | Test Conditions                                                                                      | Min. | Typ.* | Max. | Unit          |
|----------|---------------------------|------------------------------------------------------------------------------------------------------|------|-------|------|---------------|
| $I_{OH}$ | HIGH Level Output Current | $V_{CC} = 5.5\text{V}$ , $V_O = 5.5\text{V}$ ,<br>$I_F = 250\mu\text{A}$ , $V_E = 2.0\text{V}^{(2)}$ |      |       | 100  | $\mu\text{A}$ |
| $V_{OL}$ | LOW Level Output Current  | $V_{CC} = 5.5\text{V}$ , $I_F = 5\text{mA}$ , $V_E = 2.0\text{V}$ ,<br>$I_{CL} = 13\text{mA}^{(2)}$  |      | .35   | 0.6  | V             |
| $I_{FT}$ | Input Threshold Current   | $V_{CC} = 5.5\text{V}$ , $V_O = 0.6\text{V}$ , $V_E = 2.0\text{V}$ ,<br>$I_{OL} = 13\text{mA}$       |      | 3     | 5    | mA            |

**Isolation Characteristics** ( $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$  unless otherwise specified.)

| Symbol    | Characteristics                         | Test Conditions                                                                                               | Min. | Typ.*     | Max. | Unit          |
|-----------|-----------------------------------------|---------------------------------------------------------------------------------------------------------------|------|-----------|------|---------------|
| $I_{I-O}$ | Input-Output Insulation Leakage Current | Relative humidity = 45%,<br>$T_A = 25^\circ\text{C}$ , $t = 5\text{s}$ ,<br>$V_{I-O} = 3000\text{VDC}^{(12)}$ |      |           | 1.0* | $\mu\text{A}$ |
| $V_{ISO}$ | Withstand Insulation Test Voltage       | $RH < 50\%$ , $T_A = 25^\circ\text{C}$ ,<br>$I_{I-O} \leq 2\mu\text{A}$ , $t = 1\text{ min.}^{(12)}$          | 2500 |           |      | $V_{RMS}$     |
| $R_{I-O}$ | Resistance (Input to Output)            | $V_{I-O} = 500\text{V}^{(12)}$                                                                                |      | $10^{12}$ |      | $\Omega$      |
| $C_{I-O}$ | Capacitance (Input to Output)           | $f = 1\text{MHz}^{(12)}$                                                                                      |      | 0.6       |      | pF            |

\*All Typicals at  $V_{CC} = 5\text{V}$ ,  $T_A = 25^\circ\text{C}$ **Notes:**

1. The  $V_{CC}$  supply to each optoisolator must be bypassed by a  $0.1\mu\text{F}$  capacitor or larger. This can be either a ceramic or solid tantalum capacitor with good high frequency characteristic and should be connected as close as possible to the package  $V_{CC}$  and GND pins of each device.
2. Each channel.
3. Enable Input – No pull up resistor required as the device has an internal pull up resistor.
4.  $t_{PLH}$  – Propagation delay is measured from the  $3.75\text{mA}$  level on the HIGH to LOW transition of the input current pulse to the  $1.5\text{V}$  level on the LOW to HIGH transition of the output voltage pulse.
5.  $t_{PHL}$  – Propagation delay is measured from the  $3.75\text{mA}$  level on the LOW to HIGH transition of the input current pulse to the  $1.5\text{V}$  level on the HIGH to LOW transition of the output voltage pulse.
6.  $t_r$  – Rise time is measured from the 90% to the 10% levels on the LOW to HIGH transition of the output pulse.
7.  $t_f$  – Fall time is measured from the 10% to the 90% levels on the HIGH to LOW transition of the output pulse.
8.  $t_{ELH}$  – Enable input propagation delay is measured from the  $1.5\text{V}$  level on the HIGH to LOW transition of the input voltage pulse to the  $1.5\text{V}$  level on the LOW to HIGH transition of the output voltage pulse.
9.  $t_{EHL}$  – Enable input propagation delay is measured from the  $1.5\text{V}$  level on the LOW to HIGH transition of the input voltage pulse to the  $1.5\text{V}$  level on the HIGH to LOW transition of the output voltage pulse.
10.  $CM_H$  – The maximum tolerable rate of rise of the common mode voltage to ensure the output will remain in the HIGH state (i.e.,  $V_{OUT} > 2.0\text{V}$ ). Measured in volts per microsecond ( $\text{V}/\mu\text{s}$ ).
11.  $CM_L$  – The maximum tolerable rate of rise of the common mode voltage to ensure the output will remain in the LOW output state (i.e.,  $V_{OUT} < 0.8\text{V}$ ). Measured in volts per microsecond ( $\text{V}/\mu\text{s}$ ).
12. Device considered a two-terminal device: Pins 1, 2, 3 and 4 shorted together, and Pins 5, 6, 7 and 8 shorted together.

## Typical Performance Curves

Fig.1 Low Level Output Voltage vs. Ambient Temperature




Fig. 2 Input Diode Forward Voltage vs. Forward Current




Fig.3 Switching Time vs. Forward Current




Fig. 4 Low Level Output Current vs. Ambient Temperature




Fig. 5 Input Threshold Current vs. Ambient Temperature





Fig. 6 Output Voltage vs. Input Forward Current



## Typical Performance Curves (Continued)

Fig. 7 Pulse Width Distortion vs. Temperature




Fig. 8 Rise and Fall Time vs. Temperature




Fig. 9 Enable Propagation Delay vs. Temperature




Fig. 10 Switching Time vs. Temperature





Fig. 11 High Level Output Current vs. Temperature



## Test Circuits




Fig. 12 Test Circuit and Waveforms for  $t_{PLH}$ ,  $t_{PHL}$ ,  $t_r$  and  $t_f$




Fig. 13 Test Circuit  $t_{EHL}$  and  $t_{ELH}$

## Test Circuits (Continued)





Fig. 14 Test Circuit Common Mode Transient Immunity



## Ordering Information


| Option | Example Part Number | Description                           |
|--------|---------------------|---------------------------------------|
| S      | 6N137S              | Surface Mount Lead Bend               |
| SD     | 6N137SD             | Surface Mount; Tape and Reel          |
| W      | 6N137W              | 0.4" Lead Spacing                     |
| V      | 6N137V              | VDE0884                               |
| WV     | 6N137WV             | VDE0884; 0.4" Lead Spacing            |
| SV     | 6N137SV             | VDE0884; Surface Mount                |
| SDV    | 6N137SDV            | VDE0884; Surface Mount; Tape and Reel |

## Marking Information




| Definitions |                                                                                        |
|-------------|----------------------------------------------------------------------------------------|
| 1           | Fairchild logo                                                                         |
| 2           | Device number                                                                          |
| 3           | VDE mark (Note: Only appears on parts ordered with VDE option – See order entry table) |
| 4           | Two digit year code, e.g., '03'                                                        |
| 5           | Two digit work week ranging from '01' to '53'                                          |
| 6           | Assembly package code                                                                  |




## Tape Specifications



## Reflow Profile





- Peak reflow temperature: 225C (package surface temperature)
- Time of temperature higher than 183C for 60–150 seconds
- One time soldering reflow is recommended





NOTES:

- A) NO STANDARD APPLIES TO THIS PACKAGE
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSION
- D) DRAWING FILENAME AND REVISION: MKT-N08GREV7






LAND PATTERN RECOMMENDATION





NOTES:

- A) NO STANDARD APPLIES TO THIS PACKAGE
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSION
- D) DRAWING FILENAME AND REVSION: MKT-N08Hrev7.





15.0° (MAX)



NOTES:

- A) NO STANDARD APPLIES TO THIS PACKAGE
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSION
- D) DRAWING FILENAME AND REVISION: MKT-N08REV7





## TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™  
AttitudeEngine™  
Awinda®  
AX-CAP®\*  
BitSiC™  
Build it Now™  
CorePLUS™  
CorePOWER™  
CROSSVOLT™  
CTL™  
Current Transfer Logic™  
DEUXPEED®  
Dual Cool™  
EcoSPARK®  
EfficientMax™  
ESBC™  
F®  
Fairchild®  
Fairchild Semiconductor®  
FACT Quiet Series™  
FACT®  
FastvCore™  
FETBench™  
FPS™

F-PFS™  
FRFET®  
Global Power Resource™  
GreenBridge™  
Green FPS™  
Green FPS™ e-Series™  
Gmax™  
GTO™  
IntelliMAX™  
ISOPLANAR™  
Making Small Speakers Sound Louder and Better™  
MegaBuck™  
MICROCOUPLER™  
MicroFET™  
MicroPak™  
MicroPak2™  
MillerDrive™  
MotionMax™  
MotionGrid®  
MTI®  
MTX®  
MVN®  
mWSaver®  
OptoHit™  
OPTOLOGIC®

OPTOPLANAR®  
Power Supply WebDesigner™  
PowerTrench®  
PowerXS™  
Programmable Active Droop™  
QFET®  
QS™  
Quiet Series™  
RapidConfigure™  
Saving our world, 1mW/W/kW at a time™  
SignalWise™  
SmartMax™  
SMART START™  
Solutions for Your Success™  
SPM®  
STEALTH™  
SuperFET®  
SuperSOT™-3  
SuperSOT™-6  
SuperSOT™-8  
SupreMOS®  
SyncFET™  
Sync-Lock™

SYSTEM GENERAL®\*  
TinyBoost®  
TinyBuck®  
TinyCalc™  
TinyLogic®  
TINYOPTO™  
TinyPower™  
TinyPWM™  
TinyWire™  
TranSiC™  
TriFault Detect™  
TRUECURRENT®\*  
μSerDes™  
SerDes®  
UHC®  
Ultra FRFET™  
UniFET™  
VCX™  
VisualMax™  
VoltagePlus™  
XS™  
Xsens™  
仙童®

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. TO OBTAIN THE LATEST, MOST UP-TO-DATE DATASHEET AND PRODUCT INFORMATION, VISIT OUR WEBSITE AT [HTTP://WWW.FAIRCHILDSEMI.COM](http://www.fairchildsemi.com). FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## AUTHORIZED USE

Unless otherwise specified in this data sheet, this product is a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability. This product may not be used in the following applications, unless specifically approved in writing by a Fairchild officer: (1) automotive or other transportation, (2) military/aerospace, (3) any safety critical application – including life critical medical equipment – where the failure of the Fairchild product reasonably would be expected to result in personal injury, death or property damage. Customer's use of this product is subject to agreement of this Authorized Use policy. In the event of an unauthorized use of Fairchild's product, Fairchild accepts no liability in the event of product failure. In other respects, this product shall be subject to Fairchild's Worldwide Terms and Conditions of Sale, unless a separate agreement has been signed by both Parties.

## ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Terms of Use

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status        | Definition                                                                                                                                                                                          |
|--------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.                                               |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.                                                    |

Rev. I77