

Product Overview

LV8732V: Stepper Motor Driver, PWM, Constant Current Control

For complete documentation, see the data sheet.

The LV8732V is a 2-channel H-bridge driver IC that can switch a stepper motor driver, which is capable of micro-step drive and supports 2W 1-2 phase excitation, and two channels of a brushed motor driver, which supports forward, reverse, brake, and standby of a motor. It is ideally suited for driving brushed DC motors and stepper motors used in office equipment and amusement applications.

Features

- Low on resistance (upper side : 0.3Ω; lower side : 0.25Ω; total of upper and lower : 0.55Ω; Ta = 25°C, IO = 2A)
- Excitation mode can be set to 2-phase, 1-2 phase, W1-2 phase, or 2W1-2 phase
- Motor current selectable in four steps
- Output short-circuit protection circuit (selectable from latch-type or auto-reset-type) incorporated
- No control power supply required
- CLK-IN Input
- Single-channel PWM current control stepper motor driver (selectable with DC motor driver channel 2) incorporated.
- BiCDMOS process IC
- Excitation step proceeds only by step signal input
- Unusual condition warning output pins

For more features, see the data sheet

Benefits

- High Efficiency
- Various Step Adjustment Available
- Low Consumption
- Safety Design
- Easy Design
- Easy Control for Micro-step Drive

Applications

- Stepper/Brush DC Motors
- Computing & Peripherals
- Industrial

End Products

- Printers
- Flatbed Scanner
- Inkjet Printer
- Multi-Function Printer
- Document Scanner

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	V _M Min (V)	V _M Max (V)	V _{CC} Min (V)	V _{CC} Max (V)	I _O Max (A)	I _O Peak Max (A)	Step Resolution	Control Type	Current Sense	Fault Detection	Package Type
LV8732V-TLM-H	3.5495	Pb-free Halide free	Active	9	32	9	32	2	2.5	1/4	Parallel	External Resistor	Over-Current	SSOP-44K EP

For more information please contact your local sales support at www.onsemi.com.

Created on: 6/1/2020