

CATALOG

Relays

➔ Industrial Relays (General Purpose)


T92S11D22-12 ✓ [Active](#)
**Directive 2002/95/EC
Compliant**
[RoHS Compliant](#)
(Corporate P/N: 9-1393211-3)
[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
General Info Sales Info	Pricing & Availability	Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)
[Schematic](#)
[PCB Layout](#)
[Wiring Diagram](#)

Searchable Features:

Brand:	Potter & Brumfield
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Processes:	Wave solder capable to 240°C
Series:	T92
Contact Arrangement:	2 Form C, DPDT, 2 C/O
Contact Current Rating (Amps.):	30
Coil Magnetic System:	Monostable
Coil Suppression Diode:	Without
Coil Selection Criteria:	Nominal Voltage
Coil Resistance (•):	86
Actuating System:	DC
Coil Latching:	Without
Coil Power, Nominal (W):	1.70

Other Properties:

RoHS/ELV Compliance History:	Altered to comply with RoHS directive
Approx. Dimensions (L x W x H) (mm [in]):	52.30 x 34.50 x 30.70 [2.060 x 1.359 x 1.209]
Coil Insulation Classification:	UL Class F
Polarized:	No
Wiring Diagram:	2 Form C
Approved Standards:	UL Recognized, UL Listed, CSA Certified, CSA Component Acceptance, VDE Component Mark

Cross Reference

[Competitive Products](#)
[Military Spec P/Ns](#)
[Tyco Brand P/Ns](#)

- ➔ [Part Number Search](#)
- ➔ [Document Search](#)
- ➔ [Product Type Search](#)
- ➔ [Product Family Search](#)
- ➔ [Alphabetical Search](#)
- ➔ [RoHS/ELV Compliance & Alternates](#)
- ➔ [CAD Model Search](#)
- ➔ [Brand Search](#)
- ➔ [Tool Search](#)
- ➔ [Multiple Part Comparison](#)
- ➔ [Lead Free Solutions](#)
- ➔ [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
click here

Mounting Options:	Flange Mount
Termination Type:	.250 x .032 Quick Connect Terminals
Input Voltage (VDC):	12
Enclosure:	Sealed
FCC Part 68 Isolation:	No
Relay Type:	PCB
LED Indicator:	Without
Contact Material:	Silver Cadmium Oxide

[Copyright](#) and [Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]

■