

## CATALOG

### Cross Reference

[Competitive Products](#)  
[Military Spec P/Ns](#)  
[Tyco Brand P/Ns](#)


- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter  
**SUBSCRIBE NOW!**  
click here

## Relays

### Industrial Relays (General Purpose)


**T92S7D22-24**  [Active](#)
**(Tyco Electronics P/N: 1-1393212-7)**
[Not ELV or RoHS Compliant](#)
[Search for Compliant \(RoHS/ELV\)](#)
[Alternates](#)
[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

### Related Part Information

General Information	eCommerce	Related Part Information
<a href="#">General Info</a> <a href="#">Sales Info</a>	<a href="#">Pricing</a> <a href="#">Product Availability</a>	<a href="#">Tooling</a>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)
[Schematic](#)
[PCB Layout](#)
[Wiring Diagram](#)

### Searchable Features:

<b>Brand:</b>	Potter & Brumfield
<b>RoHS/ELV Compliance:</b>	Not ELV/RoHS compliant
<b>Lead Free Solder Processes:</b>	Not relevant for lead free process
<b>Series:</b>	T92
<b>Contact Arrangement:</b>	2 Form A, DPST-NO, 2 N/O
<b>Contact Current Rating (Amps.):</b>	30
<b>Coil Magnetic System:</b>	Monostable
<b>Coil Suppression Diode:</b>	Without
<b>Coil Selection Criteria:</b>	Nominal Voltage
<b>Coil Resistance (<math>\Omega</math>):</b>	350
<b>Actuating System:</b>	DC

### Other Properties:

<b>Approx. Dimensions (L x W x H) (mm [in]):</b>	52.30 x 34.50 x 30.70 [2.060 x 1.359 x 1.209]
<b>Coil Insulation Classification:</b>	UL Class F
<b>Polarized:</b>	No
<b>Wiring Diagram:</b>	2 Form A
<b>Approved Standards:</b>	UL Recognized, UL Listed, CSA Certified, CSA Component Acceptance, VDE Component Mark

<b>Coil Latching:</b>	Without
<b>Coil Power, Nominal (W):</b>	1.70
<b>Mounting Options:</b>	Flange Mount
<b>Termination Type:</b>	.250 x .032 Quick Connect Terminals
<b>Input Voltage (VDC):</b>	24
<b>Enclosure:</b>	Sealed
<b>FCC Part 68 Isolation:</b>	No
<b>Relay Type:</b>	PCB
<b>LED Indicator:</b>	Without
<b>Contact Material:</b>	Silver Cadmium Oxide

[Copyright](#) and [Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]