

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFDynamic Cabl..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Current refinements (click to remove) Search Tips

Text Search: 'ABDCM30-AV-C'

Your search criteria matched only one product, shown below

**PLEASE
SEE THE
DESCRIPTION**

- High bond adhesive provides maximum adhesion, especially in harsh, high temperature, outdoor environments; extending service life
- Smooth surfaces and rounded edges protect the cable bundle and the installer; improving productivity, job site safety, and reliability
- Flexible, lightweight material is easily handled; improving productivity

Part Number	ABDCM30AV-C
RoHS Compliancy Status	Compliant
Part Description	High Bond Dynamic Cable Manager for Panel Strain Relief
Product Type	Cable Tie Mounts- Adhesive Backed
Material	Nylon 6.6
Color	White
Height (In.)	0.66
Height (mm)	16.8
Length (In.)	1.12
Length (mm)	28.4
Width (In.)	1.12
Width (mm)	28.4
Adhesive Type	VHB
Environment	Indoor/High Temp
Mounting Method	VHB Adhesive Tape
Overall Size W x H (In.)	1.98 x 0.66
Overall Size W x H (mm)	50.3 x 16.8
Pricing Description	Dynamic Cable Manager, VHB Adh, 1.12" x 1.12" (28.4mm x 28.4mm), Nylon 6.6, Nat
Temperature Range	-31°F– 185°F (-35°C– 85°C)
Type	Cable Tie Mounts- Adhesive Backed
Used With Cable Ties	M, I, S
Min. Order UOM	PC
Min. Order Qty.	100
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.