



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
 - PDFTAK-TY Hook ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'ABMT-S6-C69'

Your search criteria matched only one product, shown below

ABMT-S6-C69



- Used with *PANDUIT*® cable ties for a complete wire routing solution
- Adhesive backing allows routing of wires and cables where mounting holes cannot be drilled
- Tear tab provides fast and easy liner removal to speed installation
- For indoor use

‡ Cable Tie Cross Section Sizes: M = Miniature, I = Intermediate, S = Standard, HS = Heavy - Standard, LH = Light-Heavy, H = Heavy, HLM = Miniature*Tak-Ty*® Hook & Loop Ties.

* Flame retardant products are manufactured from a material that is rated UL94V -0.

	Part Number	ABMT-S6-C69
	RoHS Compliancy Status	Compliant
	Part Description	Screw applied mount for use with <i>Tak-Ty</i> ® Hook & Loop Cable Ties.
	Material	Flame Retardant Nylon 6.6
	Color	Natural
	Height (In.)	.34
	Height (mm)	8.4
	Length (In.)	1.12
	Length (mm)	28.5
	Width (In.)	1.12
	Width (mm)	28.6
	CE Compliant	No
	CE Marking	No
	Environment	Indoors
	Flammability Rating	UL94 V-0
	Max. Bundle Diameter (mm)	19.1
	Mounting Method	#6 (M3) Screw
	Pricing Description	Cable Tie Mount, #6 Screw (M3), 1.12"x1.12" (28.5mm x 28.5mm), <i>FRIAT</i>
	Screw Size	#6 (M3)
	Screw Size Metric	M3
	Used With Cable Ties	HTL/HLS TakTy® Hook & Loop Cable Ties
	Min. Order UOM	PC
	Min. Order Qty.	100
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.