Search Results

Evaluate
- FAQ's
Design a Solution
- Catalog Cut Sheet
- PDF BS100445 Pro
- Part Drawings
- PDF Braided Bond ..
- Specification Sheets
- PDF StructuredGr ..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'BS100445'**

Your search criteria matched only one product, shown below

BS100445



- Used to electrically bond enclosure doors, motors, and machine frames in the construction of control panels or machine structures
- Flat ferrule end design helps to reduce the effects of EMI (Electromagnetic Interference)
- Available with internationally recognized green and yellow insulation for grounding application
- Made of high conductivity copper and tin-plated to inhibit corrosion
- Seamless ferrule ends provide mechanical strength for improved reliability
- UL 467 Listed and CSA Certified

Part Number	BS100445
RoHS Compliancy Status	Compliant
Part Description	Braided Bonding Strap, onehole, insulated, 4.00" length x 1.06" width (101.6mm x 27.0mm).
Depth (In.)	3.00
Depth (mm)	76.2
Height (In.)	4.00
Height (mm)	101.6
Length (In.)	4.00
Length (mm)	101.6
Width (In.)	1.06
Width (mm)	27.0
Copper Conductor Size	#4 AWG
Stud Hole Size (In.)	3/8
Ferrule Length (In.)	1.00
Ferrule Length (mm)	25.4
Pricing Description	Braided Bonding Strap, OneHole, Insulated, 4" x 1.06" (101.6mm x 27.0mm)
Stud Hole Size (mm)	M10
Thickness (In.)	0.13
Thickness (mm)	3.3
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy