Search Results

Evaluate
- FAQ's
Design a Solution
- Catalog Cut Sheet
- PDF BS100445 Pro
- Part Drawings
- PDF Braided Bond ..
- Specification Sheets
- PDF StructuredGr ..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'BS100645U'**

Your search criteria matched only one product, shown below

BS100645U

- Used to electrically bond enclosure doors, motors, and machine frames in the construction of control panels or machine structures
- Flat ferrule end design helps to reduce the effects of EMI (Electromagnetic Interference)
- Available with internationally recognized green and yellow insulation for grounding application
- Made of high conductivity copper and tin-plated to inhibit corrosion
- Seamless ferrule ends provide mechanical strength for improved reliability

Part Number	BS100645U
RoHS Compliancy Status	Compliant
Part Description	Braided Bonding Strap, one hole, non-insulated, 6.00" length x 1.06" width (152.4mm x 27.0mm).
Depth (In.)	5.00
Depth (mm)	127.0
Height (In.)	6.00
Height (mm)	152.4
Length (In.)	6.00
Length (mm)	152.4
Width (In.)	1.06
Width (mm)	27.0
Copper Conductor Size	#4 AWG
Stud Hole Size (In.)	3/8
Ferrule Length (In.)	1.00
Ferrule Length (mm)	25.4
Pricing Description	Braided Bonding Strap, One Hole, Non-Insulated, 6" x 1.06" (152.4mm x 27.0mm)
Stud Hole Size (mm)	M10
Thickness (In.)	0.13
Thickness (mm)	3.3
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy