

- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click to remove) Search Tips

Text Search: 'BS100845U'

Your search criteria matched only one product, shown below

- Used to electrically bond enclosure doors, motors, and machine frames in the construction of control panels or machine structures
- Flat ferrule end design helps to reduce the effects of EMI (Electromagnetic Interference)
- Available with internationally recognized green and yellow insulation for grounding applications
- Made of high conductivity copper and tin-plated to inhibit corrosion
- Seamless ferrule ends provide mechanical strength for improved reliability

Part Number	BS100845U
RoHS Compliancy Status	Compliant
Part Description	Braided Bonding Strap, onehole, non-insulated, 8.00" length x 1.06" width (203.2mm x 27.0mm).
Depth (In.)	7.00
Depth (mm)	177.8
Height (In.)	8.00
Height (mm)	203.2
Length (In.)	8.00
Length (mm)	203.2
Width (In.)	1.06
Width (mm)	27.0
Copper Conductor Size	#4 AWG
Stud Hole Size (In.)	3/8
Ferrule Length (In.)	1.00
Ferrule Length (mm)	25.4
Pricing Description	Braided Bonding Strap, OneHole, NonInsulated, 8" x 1.06" (203.2mm x 27.0mm)
Stud Hole Size (mm)	M10
Thickness (In.)	0.13
Thickness (mm)	3.3
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.