Search Results

Evaluate
- FAQ's
- Selection Guides
- PDF-Convenience ..

Design a Solution
- Part Drawings
- PDF-Butt Splices ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'BSN10-E'**

Your search criteria matched only one product, shown below

BSN10-E

- Designed to splice two solid or stranded wires together to repair or lengthen wires
- Butted configuration provides low profile for limited space applications
- Brazed seam protects terminal barrel from splitting during the crimp process
- Internal wire stop assures proper length of insertion into terminal barrel
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486C, where applicable

Part Number	BSN10-E
RoHS Compliancy Status	Compliant
Part Description	Butt Splice 12 – 10 AWG, nylon insulated.
Product Type	Splices
CSA Certified	Yes
UL Listed	Yes
Length (In.)	1.14
Length (mm)	29.0
CE Compliant	No
Insulation	Nylon
Max. Ins.	0.210
Max. Ins. (mm)	5.3
Panduit Color Code	Yellow
Plating Type	Tinned
Pricing Description	Terminal Convenience Package
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-100A, CT-600-A, CT-1550, CT-1551, CT-2500
Wire Range	12 – 10 AWG
Wire Range (mm^2)	4.0 – 6.0
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy