Search Results

Evaluate
- FAQ's
- Selection Guides
- PDF Heat Shrink..

Design a Solution
- Catalog Cut Sheet
- PDF HSEC0.5X Pr
- Part Drawings
- PDF Heat Shrink..
- Specification Sheets
- PDF Thick Wall P..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ Text Search: 'HSECFR1.0XY'

Your search criteria matched only one product, shown below

HSECFR1.0-XY

• Heat indicating line ensures correct temperature is applied
• Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
• Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
* Flame retardant products are manufactured from a material that is rated UL94V -0.

Part Number	HSECFR1.0XY
RoHS Compliancy Status	Compliant
Note	HSECFR1.0XY replaces HSECFR1.0X
Part Description	Flame Retardant Thick Wall End Caps
Material	Flame retardant cross-linked polyolefin with adhesive
Color	Black
Copper Conductor Size Range	#1 – #3/0 MCM
Cap Length (In.)	3.0
Cap Length (mm)	76.2
CE Compliant	No
Conductor Size Range (mm²)	35 – 95
Flammability Rating	V-0
Max. Recovered I.D. (In.)	0.35
Max. Recovered I.D. (mm)	8.9
Min. Expanded I.D. (In.)	1.10
Min. Expanded I.D. (mm)	27.9
Nominal Recovered Wall Thickness (In.)	0.12
Nominal Recovered Wall Thickness (mm)	3.0
Pricing Description	Heat Shrink Thick Adhesive End Cap, 1"(26mm)
Temperature Range	-67°F – 230°F (-55°C – 110°C)
Type	WET-SHRINK Heat Shrink End Cap Flame Retardant Adhesive Lined
Min. Order UOM	PC
Min. Order Qty.	10
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy