



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#)

Text Search: 'HSECFR1.55Y'

Your search criteria matched only one product, shown below

HSECFR1.55Y



- Heat indicating line ensures correct temperature is applied
 - Cross -linked, UV resistant material improves flame retardancy, chemical, and temperature resistance
 - Shrink ratio of 3:1 insulates a wide range of diameters and irregular shapes, which reduces inventory costs
- * Flame retardant products are manufactured from a material that is rated UL94V -0.

	Part Number	HSECFR1.55Y
	RoHS Compliancy Status	Compliant
	Note	HSECFR1.55Y replaces HSECFR1.55
	Part Description	Flame Retardant Thick Wall End Caps
	Material	Flame retardant cross-linked polyolefin with adhesive
	Color	Black
	Copper Conductor Size Range	#2/0 – #350 MCM
	Cap Length (In.)	4.50
	Cap Length (mm)	114.3
	CE Compliant	No
	CE Marking	No
	Conductor Size Range (mm ²)	120 to 240
	Max. Recovered I.D. (In.)	.47
	Max. Recovered I.D. (mm)	11.9
	Min. Expanded I.D. (In.)	1.50
	Min. Expanded I.D. (mm)	38.1
	Nominal Recovered Wall Thickness (In.)	.160
	Nominal Recovered Wall Thickness (mm)	4.1
	Pricing Description	Heat Shrink Thick Adhesive End Cap, 1.6"(40mm)
	Temperature Range	-67°F to 230°F (55°C to 110°C)
	Min. Order UOM	PC
	Min. Order Qty.	5
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.