

[support](#) | [locate distributor](#) | [about](#) |*World Leader in Network and Electrical Solutions*[HOME](#) | [SOLUTIONS](#) | [RESOURCES](#) | [PRODUCTS](#) | [SERVICES](#) | [LEARNING](#)SEARCH Current refinements (click ☐ to remove)☒ **Region** ▶ **USA** ☒ **Product Family** ▶ **Pan-Ty® Flame Retardant Cable Ties** ☒ **Text Search:** 'PLT1M-M60'**Your search criteria matched only one product, shown below.**

- Flame Retardant Nylon 6.6 meets the requirements of UL94V-0
- Can be used with flame retardant cable tie mounts

[Relat](#)
[Cable](#)
[Cable](#)
[Pneur](#)
[4-Way](#)
[Cable](#)

Part Number:	PLT1M-M60
Product Family:	Pan-Ty® Flame Retardant Cable Ties
Product Line:	Nylon Cable Ties
RoHS Compliancy Status:	Compliant
Part Description:	Cable Tie, 4.0", Miniature cross section
Product Type:	Cable Ties
Material:	Flame Retardant Nylon 6.6
Color:	Black
CSA Certified:	No
UL Listed (File #E56854):	No
UL Recognized (File #E56854):	No
Length (In.):	4.0
Length (mm):	102
Width (In.):	.098
Width (mm):	2.5
CE Compliant:	Yes
Cross Section:	Miniature
Head Height (In.):	.154
Head Height (mm):	3.9
Head Width (In.):	.188
Head Width (mm):	4.8
Locking Style:	Locking
Material Flammability Rating:	UL94V-0
Max. Bundle Diameter (In.):	.87
Max. Bundle Diameter (mm):	22
Max. Continuous Use Temperature:	212°F (100°C)
Min. Loop Tensile Strength (Lbs.):	18
Min. Loop Tensile Strength (N):	80

Product Family: *Pan-Ty®* Flame Retardant Cable Ties
Record Type: Products
Std. Pkg. UOM: PK
Thickness (In.): .043
Thickness (mm): 1.1
Tool: GTS, GTSL, GS2B, PTS, PPTS, STS2
UOM: PC
Std. Pkg. Qty.: 1000
Min. Order Qty.: 1000
Part Number: PLT1M-M60
BOM Qty. (# of Pkgs.)
Add to My Catalog ☐

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

[View Content Details](#)

[Evaluate](#)

[Design a Solution](#)

[Instal](#)

Part Drawings:



[Pan-Ty Flame Retardant Cable Tie, Blac...](#)

[legal information](#) | [privacy policy](#) | [site map](#)

Copyright © 1995-2006, PANDUIT CORP. All rights reserved.