



80W Constant Voltage LED Driver PDA080 Series for Outdoor Lighting



Features

- High Efficiency
- UL8750 Compliant
- 5 Year Warranty
- OVP, Short and Open Circuit Protection
- IP65, Potted
- Wide Operating Temperature Range
- Brownout/Brownout Recovery
- 120V-277V AC Operation

Applications

- General Lighting
- Street Lighting
- Outdoor Lighting
- Architectural Lighting

Safety Approvals (PENDING)

- CE
- cUL/UL

Mechanical Characteristics

- Length: 241mm (9.5in)
- Width: 43mm (1.7in)
- Height: 30.5mm (1.2in)
- Weight: 750g (1.65lbs)

Output Specifications

Model	Output Voltage	Output Current			Output Power
		Min.	Typ.	Max.	
PDA080B-48VG	48V	0A	1.67A	1.70A	80W

PhiHong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

Input:**AC Input Voltage Rating**

100VAC to 277VAC

AC Input Frequency

47~63Hz

Maximum Input Current $\leq 2A$ **Leakage Current**

0.5mA maximum at 230VAC Input

Inrush Current $\leq 20A$ **OUTPUT:****Power Factor** ≥ 0.9 at nominal**Ripple and Noise** $<7\%$ (p-p)**Efficiency (Target)**

88% at 277VAC

84% at 120VAC

Turn-on Delay Time

0.5s maximum at nominal AC Power ON

Environmental:**Temperature**

Operation -40 to +60°C

Non-operation -40 to +85°C

Operating Humidity 10 to 95%

EMC

EN55015/CISPR 15, FCC 47 CFR Part 15/18, Class A

Immunity

IEC61000-4-2

IEC61000-4-3

IEC61000-4-4

IEC61000-4-5

IEC61000-4-6

IEC61000-4-8

IEC61000-4-11

IEC61000-3-2 Class C

Input Over Current Protection

The input power line will be fused with a 3.15A fuse

Short-Circuit Protection

The PSU will withstand a short circuit across the outputs without damage

Open Circuit Protection

Once the circuit is opened, the output voltage should be less than 120% at nominal AC input conditions

Dielectric Withstand (Hi-pot) Test

Primary to secondary: 4242VDC for 1 minute, 5mA

Insulation ResistancePrimary to secondary: $>5M\ \Omega$ 500VDC, 1 Minute**Design Life**50K hours at full power, ambient 50°C and $T_{case} < \text{rating}$ **Wire Connections**

Position	Terminal Color	Specification
Line	Black	AWG18 solid wire
Neutral	White	AWG18 solid wire
Ground	Green/Yellow	AWG18 solid wire
Vout+	Red	AWG18 solid wire
Vout-	Blue	AWG18 solid wire

Warranty

5 Years

