

## Plastic label - US-EMLP (100X60) SR - 0828910

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plastic label, Card, silver, unlabeled, can be labeled with: THERMOMARK PRIME, THERMOMARK CARD, BLUEMARK ID, BLUEMARK ID COLOR, mounting type: adhesive, lettering field size: 100 x 60 mm



### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 10 STK                                                                                                  |
| Minimum order quantity | 10 STK                                                                                                  |
| GTIN                   | <br>4 046356 559218 |
| GTIN                   | 4046356559218                                                                                           |

### Technical data

#### Dimensions

|            |        |
|------------|--------|
| Length (b) | 60 mm  |
| Width (a)  | 100 mm |
| Height (c) | 0.5 mm |

#### Ambient conditions

|                                 |                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation) | -30 °C ... 80 °C                                                                                        |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

#### General

|                                        |                             |
|----------------------------------------|-----------------------------|
| Color                                  | silver                      |
| Components                             | Silicone-free               |
| Flammability rating according to UL 94 | V0                          |
| Material                               | PVC                         |
| RoHS compliant                         | Yes                         |
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels            | 2                           |
| Number of individual labels per row    | 1                           |

## Plastic label - US-EMLP (100X60) SR - 0828910

### Technical data

#### General

|                                                                     |                                     |
|---------------------------------------------------------------------|-------------------------------------|
| Adhesive                                                            | Acrylic                             |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                |
| Result                                                              | Test passed                         |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03        |
| Test duration                                                       | 96 h                                |
| Wipe resistance test result                                         | Test passed                         |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02           |
| Test duration                                                       | 96 h                                |
| Salt spray testing result                                           | Test passed                         |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result                                                              | Test passed                         |
| Foil strength                                                       | 500 µm                              |
| Adhesive strength                                                   | 50 µm                               |
| Marking mounting type                                               | adhesive                            |

#### Standards and Regulations

|                                        |                             |
|----------------------------------------|-----------------------------|
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V0                          |

#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
|------------|-----------------------------------------------------------------------------------------------------|

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>