

Fuse - SI FORM C 20 A DIN 72581 - 0913744

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Flat-type plug-in fuse, type C, color code: yellow, nominal current: 20 A

Your advantages

- ✓ With snap-in foot for secure pre-assembly on the PCB
- ✓ Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V

Key Commercial Data

Packing unit	50 pc
GTIN	
GTIN	4017918104023

Technical data

General

Color	yellow
Flammability rating according to UL 94	V0

Dimensions

Width	5 mm
Length	19 mm

General

Fuse	C
Nominal current I_N	20 A
Nominal voltage U_N	24 V

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Fuse - SI FORM C 20 A DIN 72581 - 0913744

Classifications

eCl@ss

eCl@ss 10.0.1	27142008
eCl@ss 4.0	27142000
eCl@ss 4.1	27142000
eCl@ss 5.0	27142000
eCl@ss 5.1	27142000
eCl@ss 6.0	27142000
eCl@ss 7.0	27142008
eCl@ss 8.0	27142008
eCl@ss 9.0	27142008

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC002298
ETIM 4.0	EC002298
ETIM 5.0	EC002298
ETIM 6.0	EC002298
ETIM 7.0	EC002298

UNSPSC

UNSPSC 6.01	30211813
UNSPSC 7.0901	39121410
UNSPSC 11	39121412
UNSPSC 12.01	39121412
UNSPSC 13.2	39121622
UNSPSC 19.0	39121622

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.BL08.B.00724
-----	--	--------------------------

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>