

Sealing cap - PROT-M12 MS-PA-CHAIN-EYE-DM14 - 1456200

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



M12 sealing cap with fixing band, for free M12 sockets with 14.5 mm fastening eye



Key Commercial Data

| Packing unit | 5 pc |
|------------------------|-----------------|
| Minimum order quantity | 5 pc |
| GTIN | 4 046356 605724 |
| GTIN | 4046356605724 |

Technical data

Ambient conditions

| Ambient temperature (operation) | -25 °C 85 °C |
|---------------------------------|--------------|
| Degree of protection | IP67 |

General

| Note | Not suitable for M12 sockets with K, L, or M coding |
|----------|---|
| Material | |

Flammability rating according to UL 94 Material PA 6.6 GF Sealing material Additional material specifications PUR (Holding band)

Standards and Regulations

| Flammability rating according to UL 94 | V0 | |
|--|----|--|

Environmental Product Compliance

| China RoHS | Environmentally Friendly Use Period = 25; |
|------------|---|



Sealing cap - PROT-M12 MS-PA-CHAIN-EYE-DM14 - 1456200


Technical data

Environmental Product Compliance

| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
|--|---|
|--|---|

Drawings

Dimensional drawing



Dimensional drawing

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details



Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com