

Socket strip - SKBD 20/MT-FLRP - 2202505

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug component, Number of positions: 20, Pitch: 5 mm, Contact surface: Tin



Key commercial data

Packing unit	1 pc
GTIN	 4 017918 053277
Weight per Piece (excluding packing)	79.68 GRM
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Pitch	5 mm
-------	------

General

Range of articles	SKBD
Nominal cross section	2.5 mm ²
Stripping length	8 mm
Screw thread	M3
Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm
Number of positions	20

Socket strip - SKBD 20/MT-FLRP - 2202505

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260710
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152

ETIM

ETIM 3.0	EC000446
ETIM 4.0	EC002642
ETIM 5.0	EC002642

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

GOST

Ex Approvals

Approvals submitted

Approval details

GOST 
--

Socket strip - SKBD 20/MT-FLRP - 2202505

Drawings

Dimensioned drawing

