

► General data



Plug-in card block, for indirect connection in accordance with IEC 603-1/DIN 41617, complete with guide rails, engagement catches and ejector, with standardized marking on both connection sides, as well as fixing screws M 4, cross section 0.2 - 4 mm² rigid / 0.2 - 2.5 mm² flexible, 4 A, 250 V, 32-pos.

Order number	2261054
Type	SKBI 32/D
Barcode number	4017918053826
Unit pack	1 Piece
Customs tariff	85369010000

► Technical data

Dimensions / positions

Length	43 mm
Height	138 mm
Width	112 mm
Pitch	5.08 mm
Number of positions	32
Hole diameter	4.2 mm
Screw thread	M 3
Tightening torque	0.5 Nm

Technical data


Connection in acc. with standard	IEC/ DIN VDE
Nominal current I_N	4 A
Nominal voltage U_N	250 V
Stripping length	8 mm

Connection data


Min. conductor cross section, rigid	0.2 mm ²
Conductor cross section, rigid max.	4 mm ²
Conductor cross section flexible min.	0.2 mm ²
Max. conductor cross section, flexible	2.5 mm ²
Min. conductor cross section AWG/kcmil	24
Conductor cross section AWG/kcmil max	12

► Drawings

Dimensioned drawing



Schematic diagram



► Accessories

Item	Designation	Description
Assembly		
2261009	SF-SKBI 31/32	Snap foot, for horizontal or vertical mounting of the SKBI plug-in card blocks, on the NS 35/7.5 mounting rail

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved