

► General data



VARIOFACE panel feed-through module, for direct coupling of single signal lines of up to 2.5 mm², with D-Subminiature socket strip, 15-pos.

Order number	2280307
Type	DFLK-D15 SUB/B

Barcode number	4017918054410
Unit pack	5 Piece
Customs tariff	85369010000

► Technical data

General data

Nominal voltage U_N	125 V
Max. current carrying capacity per branch	2.5 A
Number of positions	15
Length	58.4 mm
Width	39 mm
Height	33 mm
Standards/regulations	IEC 664/IEC 664 A/DIN VDE 0110; DIN VDE 0160 (in parts)

Connection data

Connection 1	PCB connection
Connection in acc. with standard	IEC/ DIN VDE
Type of connection	Screw connection
Min. conductor cross section, rigid	0.2 mm ²
Conductor cross section, rigid max.	4 mm ²
Conductor cross section flexible min.	0.2 mm ²
Max. conductor cross section, flexible	2.5 mm ²
Min. conductor cross section AWG/kcmil	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M 3
Connection 2	D-SUB connection
Type of connection	Pluggable

► Certificates

UL




Nominal voltage U_N	125 V
Nominal current I_N	2.5 A
AWG/kcmil	30-12

CUL

Nominal voltage U_N	125 V
Nominal current I_N	2.5 A
AWG/kcmil	30-12

► Drawings

Dimensioned drawing



Approval logo



► Accessories

Item	Designation	Description
Cable/conductor		
2302340	CABLE D-SUB-S/.../.../...	Shielded round cable, assembled with one D-SUB socket and pin strip
2302052	CABLE-D15SUB/B/S/50/KONFEK/S	Round shielded cable set, with 15-pos. D-SUB female and male connectors, cable length: 0.5 m
2302065	CABLE-D15SUB/B/S/100/KONFEK/S	Round shielded cable set, with 15-pos. D-SUB female and male connectors, cable length: 1 m
2302078	CABLE-D15SUB/B/S/150/KONFEK/S	Round shielded cable set, with 15-pos. D-SUB female and male connectors, cable length: 1.5 m
2302081	CABLE-D15SUB/B/S/200/KONFEK/S	Round shielded cable set, with 15-pos. D-SUB female and male connectors, cable length: 2 m
2302094	CABLE-D15SUB/B/S/300/KONFEK/S	Round shielded cable set, with 15-pos. D-SUB female and male connectors, cable length: 3 m
2302104	CABLE-D15SUB/B/S/400/KONFEK/S	Round shielded cable set, with 15-pos. D-SUB female and male connectors, cable length: 4 m
2302117	CABLE-D15SUB/B/S/600/KONFEK/S	Round shielded cable set, with 15-pos. D-SUB female and male connectors, cable length: 6 m
General		
2302434	CABLE D-SUB/S/S-S/.../.../...	Shielded round cable, assembled with two D-SUB pin strips

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved