

## Monitor - BL FPM 15.6 - 2402980

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



IP65-rated, 15.6-inch, flat -panel LCD monitor with projective capacitive touch screen

### Product Description

The Baseline BL FPM 15.6 is an industrial flat-panel monitor that can be used in applications where a remote display location is required.

### Your advantages

- ✓ 15.6-inch display
- ✓ DisplayPort 1.2, VGA, and DVI-I input ports
- ✓ Integrated configuration buttons
- ✓ Ambient operating temperatures from -10°C to 60°C
- ✓ 15.6-inch touch screen display

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 055626 202297 |
| GTIN         | 4055626202297                                                                                           |

### Technical data

#### Note

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---------------------------------------------------------------------------|

#### Display

|                        |                                          |
|------------------------|------------------------------------------|
| Display                | 39.6 cm/15.6" TFT                        |
| Screen resolution      | 1366 x 768 Pixel(s) (WXGA)               |
| Touch technology       | projective-capacitive, ten-touch control |
| Brightness             | 300 cd/m², typical (adjustable)          |
| Backlighting           | LED                                      |
| Display backlight MTBF | > 50000 h                                |

# Monitor - BL FPM 15.6 - 2402980

## Technical data

### Display

|        |                     |
|--------|---------------------|
| Colors | 16.7 million colors |
|--------|---------------------|

### Monitor data

|                |                                        |
|----------------|----------------------------------------|
| Network        | Without network                        |
| Interfaces     | 1x USB Type A (For touch control only) |
| Monitor output | 1x DisplayPort                         |
|                | 1x DVI-D                               |
|                | 1x VGA                                 |
| Slots          | without slots                          |
| Optical drive  | without drive                          |

### General

|               |                    |
|---------------|--------------------|
| Mounting type | VESA MIS-D, 100    |
|               | Front installation |
| Weight        | 5.48 kg            |

### Ambient conditions

|                                         |                                |
|-----------------------------------------|--------------------------------|
| Degree of protection                    | IP65 (front), IP20 (back)      |
| Ambient temperature (operation)         | -10 °C ... 60 °C               |
| Ambient temperature (storage/transport) | -20 °C ... 75 °C               |
| Permissible humidity (operation)        | 10 % ... 90 % (non-condensing) |
| Vibration (operation)                   | 1g                             |
| Shock                                   | 15g, 11 ms impulse             |

### Device supply

|                   |                 |
|-------------------|-----------------|
| Supply voltage    | 24 V DC (±10 %) |
| Power supply unit | 24 V DC         |

### Standards and Regulations

|                       |                    |
|-----------------------|--------------------|
| Shock                 | 15g, 11 ms impulse |
| Vibration (operation) | 1g                 |

### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                      |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 19200103 |
| eCl@ss 4.0    | 24010600 |
| eCl@ss 4.1    | 24010600 |

## Monitor - BL FPM 15.6 - 2402980

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.0 | 27330200 |
| eCl@ss 5.1 | 27330200 |
| eCl@ss 6.0 | 27242300 |
| eCl@ss 7.0 | 27242301 |
| eCl@ss 8.0 | 19200201 |
| eCl@ss 9.0 | 19200103 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001425 |
| ETIM 4.0 | EC001428 |
| ETIM 5.0 | EC001428 |
| ETIM 6.0 | EC001414 |
| ETIM 7.0 | EC001414 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 43172401 |
| UNSPSC 7.0901 | 43211902 |
| UNSPSC 11     | 43172401 |
| UNSPSC 12.01  | 43211902 |
| UNSPSC 13.2   | 43211902 |
| UNSPSC 18.0   | 43211509 |
| UNSPSC 19.0   | 43211509 |
| UNSPSC 20.0   | 43211509 |
| UNSPSC 21.0   | 43211509 |

### Approvals

#### Approvals

#### Approvals

UL Listed / cUL Listed / cULus Listed

#### Ex Approvals

#### Approval details

UL Listed



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 238705

## Monitor - BL FPM 15.6 - 2402980

### Approvals

cUL Listed



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

FILE E 238705

cULus Listed



### Accessories

#### Accessories

#### Mounting material

Mounting flange - BL FPM MOUNTING KIT - 2403287



IPC mounting block style C. Compatible with BL FPM...

Connecting cable - VL 2.0M DP CABLE - 2404774



DisplayPort (DP) cable (2 m) for use with industrial computers

### Spare parts

Printed-circuit board connector - MSTB 2,5/ 3-STF - 1786844



PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm<sup>2</sup>, number of positions: 3, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>