

Monitor - VL FPM 17B - 2404325

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



17"/43 cm flat panel LCD monitor with resistive touch screen. Includes two rear USB ports.

Similar figure



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 460598
GTIN	4055626460598

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Outer dimensions: width, height, depth	452 mm x 356.5 mm x 50 mm (Includes bezel)
Installation dimensions: width, height, depth	424 mm x 329.5 mm (Panel cutout)

Display

Display	43,2 cm / 17"-TFT
Screen resolution	1280 x 1024 Pixel(s) (SXGA)
Touch technology	analog resistive (polyester)
Brightness	350 cd/m ² , typical (adjustable)
Backlighting	CCFL
Display backlight MTBF	> 50000 h
Colors	16.7 million colors

Monitor data

Network	Without network
Interfaces	1x USB 1.1, Typ A

Monitor - VL FPM 17B - 2404325

Technical data

Monitor data

	1x USB 2.0, Typ A
Monitor output	1x DVI-D
	1x VGA
Slots	without slots

General

Note	Order information: This VL FPM does not include the Phoenix Contact logo on the front panel.
Mounting type	VESA MIS-D, 100/75, C
	Front installation
Weight	6.43 kg

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	5 % ... 95 %
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Device supply

Supply voltage	24 V DC (typical)
Supply voltage range	19.2 V DC ... 28.8 V DC
Power supply unit	24 V DC ±20 %

Standards and Regulations

Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	DIN EN 60068-2-6

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0	24010601
eCl@ss 4.1	24010601
eCl@ss 5.0	27330200
eCl@ss 5.1	27330200
eCl@ss 6.0	27242300

Monitor - VL FPM 17B - 2404325

Classifications

eCl@ss

eCl@ss 7.0	27242301
eCl@ss 8.0	19200201
eCl@ss 9.0	19200103

ETIM

ETIM 3.0	EC001425
ETIM 4.0	EC001428
ETIM 5.0	EC001428
ETIM 6.0	EC001414
ETIM 7.0	EC001414

UNSPSC

UNSPSC 6.01	43172401
UNSPSC 7.0901	43211902
UNSPSC 11	43172401
UNSPSC 12.01	43211902
UNSPSC 13.2	43211902
UNSPSC 18.0	43211509
UNSPSC 19.0	43211509
UNSPSC 20.0	43211509
UNSPSC 21.0	43211509

Accessories

Accessories

Operating stylus

Touch pen - TOUCH PEN - 2701379



Touch pen for analog-resistive HMI, silver coated. Delivery includes self-adhesive pen holder.

Spare parts

Printed-circuit board connector - MSTB 2,5/ 3-STF - 1786844



PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 3, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: green, contact surface: Tin

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>