

Uninterruptible power supply - UNO-UPS/24DC/24DC/60W - 2905907

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Uninterruptible power supply with integrated power storage, lead AGM, VRLA technology, 24 V DC, 0.8 Ah.



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	1100.0 g
Country of origin	Germany

Technical data

Dimensions

Width	110 mm
Height	90 mm
Depth	84 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-15 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 60 °C
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, non-condensing)
Noise immunity	EN 61000-6-2

Input data

Nominal input voltage	24 V DC (SELV)
Current consumption (maximum)	2.8 A
Current consumption (idle)	< 60 mA
Current consumption (charging process)	< 300 mA
Input fuse, integrated	5 A (electronic)

Uninterruptible power supply - UNO-UPS/24DC/24DC/60W - 2905907

Technical data

Output data (24 V DC mains operation)

Nominal output current (I_N)	2.5 A
----------------------------------	-------

Output data (24 V DC battery operation)

Nominal output current (I_N)	2.5 A
----------------------------------	-------

General output data

Efficiency	> 95 % (Mains operation, with charged power storage)
------------	--

General

IQ technology	No
Net weight	1 kg
Memory medium	Lead rechargeable battery module
Protection class	III
MTBF (IEC 61709, SN 29500)	> 1900000 h (40°C)
Mounting position	horizontal DIN rail NS 35, EN 60715
Assembly instructions	Alignable: 0 mm horizontally, 30 mm vertically

Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	14
Stripping length	7 mm
Screw thread	M3

Connection data, output

Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	14
Stripping length	7 mm
Screw thread	M3

Connection data for signaling

Connection method	Screw connection
-------------------	------------------

Uninterruptible power supply - UNO-UPS/24DC/24DC/60W - 2905907

Technical data

Connection data for signaling

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	14
Stripping length	7 mm
Screw thread	M3

Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Noise immunity	EN 61000-6-2
Standards/regulations	EN 61000-4-2
	EN 61000-4-3
	EN 61000-4-4
	EN 61000-4-5
	EN 61000-4-6
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
UL approvals	UL Listed UL 508
	UL/C-UL Recognized UL 60950
Vibration (operation)	< 13.2 Hz, amplitude ±1.0 mm (according to IEC 60068-2-6)
	13.2 Hz ... 100 Hz, 0.7g

Classifications

eCl@ss

eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 8.0	27040603
eCl@ss 9.0	27040705

ETIM

ETIM 5.0	EC000382
----------	----------

Approvals

Approvals

Uninterruptible power supply - UNO-UPS/24DC/24DC/60W - 2905907

Approvals

Approvals

UL Listed / cUL Listed / EAC / IECEx CB Scheme / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Listed 

cUL Listed 

EAC

IECEx CB Scheme 

UL Recognized

cUL Recognized

cULus Recognized 

Accessories

Accessories

Power supply

Uninterruptible power supply - UNO-UPS/24DC/24DC/60W - 2905907

Accessories

Power supply unit - UNO-PS/1AC/24DC/ 60W - 2902992



Primary-switched UNO POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/60 W

Power supply unit - UNO-PS/1AC/24DC/100W - 2902993



Primary-switched UNO POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/100 W

Drawings

Block diagram

