

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Touch panel with 14.5 cm (5.7") graphics-capable C-STN display, 125 colors,  $320 \times 240$  pixels, 1 x Ethernet, 2 x USB, and integrated runtime of the Visu+ visualization software.

#### Why buy this product

- Short startup time
- ☑ Display available in sizes from 8.9 cm (3.8") to 38.1 cm (15")
- ✓ Visu+ RT and AX OPC server integrated as standard in all devices



## **Key Commercial Data**

Packing unit	1 pc
GTIN	4 046356 117227
Weight per Piece (excluding packing)	1633.8 g
Custom tariff number	84714100
Country of origin	Germany
Note	Made to Order (non-returnable)

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### **Dimensions**

External dimension, width	203 mm
External dimension, height	147 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	195 mm
Installation dimension, height	139 mm
Installation dimension, depth	54 mm



## Technical data

### Display

Display	14.5 cm/5.7" C-STN
Resolution	320 x 240 Pixel (QVGA)
Backlighting	CCFL
Touch screen	Resistive industrial touch screen
Colors	125 colors

### Computer data

Processor	RISC ARM9™ CPU; 200 MHz
Operating systems	Windows CE 5.0
RAM	64 MB SDRAM
Mass storage	32 MByte flash memory
Network	1 x Ethernet (10/100 Mbps), RJ45
Interfaces	2x USB Host 2.0
Bus system	without

#### General

Mounting type	Installation in front plate
---------------	-----------------------------

#### Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C 50 °C
Ambient temperature (storage/transport)	-25 °C 70 °C
Permissible humidity (operation)	20 % 85 % (non-condensing)
Permissible humidity (storage/transport)	10 % 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

## Classifications

## eCl@ss

eCl@ss 4.0	27330202
eCl@ss 4.1	27330202
eCl@ss 5.0	27242215
eCl@ss 5.1	27242301
eCl@ss 6.0	27242301
eCl@ss 7.0	27242301
eCl@ss 8.0	27242302

### **ETIM**

ETIM 2.0	EC001426
ETIM 3.0	EC001426
ETIM 4.0	EC001426



# Classifications

ETIM	
ETIM 5.0	EC001414
UNSPSC	
UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43211903
UNSPSC 13.2	43201404
Approvals	
Approvals	
Approvals	
UL Listed / cUL Listed / LR / GL / BV / DNV / ABS / GI	L-SW / EAC / LR / ABS / RINA / GL / cULus Listed
Ex Approvals	
Approvals submitted	
Approval details	
UL Listed (II)	
cUL Listed **	
LR	
GL	
BV	
DNV	



# Approvals

ABS
GL-SW
EAC
LR
ABS
RINA
GL
cULus Listed (ULus Ulus Listed (Ulus Ulus Listed (Ulus Ulus Ulus Ulus Ulus Ulus Ulus Ulus
Accessories
Accessories
Battery module
Battery - HMI BATTERY - 2701383
•
Lithium battery
Ethian satisfy
Mounting motorial
Mounting material
Mounting kit - HMI WALL MOUNTING KIT - 2701380
HMI mounting kit for panel installation. The mounting kit includes 2 spring clips.

138



#### Accessories

Mounting kit - HMI SCB MOUNTING KIT 4 - 2701384



HMI mounting kit for installation on a front plate. The mounting kit includes 4 x mounting brackets, 4 x screw threads, and a hexagonal wrench.

#### Mounting kit - HMI SCB MOUNTING KIT 6 - 2701385



HMI mounting kit for installation on a front plate. The mounting kit includes 6 x mounting brackets, 6 x screw threads, and a hexagonal wrench.

#### Mounting kit - HMI SCB MOUNTING KIT 8 - 2701387



HMI mounting kit for installation on a front plate. The mounting kit includes 8 x mounting brackets, 8 x screw threads, and a hexagonal wrench.

### Operating stylus

Touch pen - TOUCH PEN - 2701379



Touch pen for HMIs, silver coated. Delivery includes self-adhesive pen holder.

#### Protective foil

Protective foil - 5,7" DISPLAY PROTECTIVE FOIL - 2701371

Protective film set comprising 10 pieces of film for a 5.7" display. Including a squeegee to apply film and instructions.



Storage medium



### Accessories

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

Phoenix Contact 2015 © - all rights reserved http://www.phoenixcontact.com