

MS-328-7



MS-328-7

Normally Closed Reed Sensor

Electrical Characteristics

@ 25 °C

Contact form		B
Contact rating max.	W / VA	5
Switching voltage max.	VDC	175
	VAC	120
Switching current max.	A	0.25
Carry current max.	A	1.5
Breakdown voltage min.	VDC	200
Total resistance max. (initial)	mΩ	200
Insulation resistance min.	Ω	10 ⁹

Features

- Adjustable switching point
- Customized types available
- Various sensitivity ranges available
- Non pole oriented actuation

Magnetical Characteristics (of unmodified Reed Switch)

@ 25 °C

Pull in range available	AT	15 - 30
Drop out min.	AT	5
Test coil	TC -	200
Test equipment tolerance	± AT	2

Operating Characteristics (of unmodified Reed Switch)

@ 25 °C

Switching frequency max.	Hz	100
Resonant frequency typ.	Hz	1100
Operate time max. (incl. bounce)	ms	0.7
Release time max.	ms	1

Approvals



Environmental Characteristics

Operating temperature	°C	-20 to + 85
Vibration (50-2000 Hz)	g	30
Shock (1/2 sin 11 ms)	g	50

Ordering Information

Packing Unit	25	pcs
Weight per piece	10.4	g
Weight per package	270	g

Standard AT Ranges

- 2 = 15 to 20 AT
- 3 = 20 to 25 AT
- 4 = 25 to 30 AT


Ordering Example

MS-328-7-2 describes MS-328-7 with 15 to 20 AT.

Remarks

When mounted onto ferromagnetic parts switching distance of MS-328-7 may reduce.
Electromagnetical influences and magnetic fields may change the switching behaviour of the sensor.

Dimensions in mm



Material Information

	Material	Colour
Housing	PA-GF	black
Cable	UL 1007/1569, AWG 20, 4 mm stripped and tinned	black
Potting compound	Epoxy	black