




THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.
© 2005, Projects Unlimited Inc.

SPECIFICATIONS

PARAMETERS	VALUES	UNITS
RATED VOLTAGE	12	Vdc
OPERATING VOLTAGE RANGE	6 ~ 28	Vdc
RATED CURRENT (MAX)	6	mA
MINIMUM SPL @ 10 CM	88	dBa
RESONANT FREQUENCY	2900±500	—
TONE OR PULSE RATE	FAST PULSE	3.2 PULSE PER SECOND
OPERATING TEMPERATURE	−20 ~ +60	°C
STORAGE TEMPERATURE	−30 ~ +70	°C
HOUSING MATERIAL	ABS	—
TERMINAL MATERIAL	Ni PLATED BRASS	—
WEIGHT	43	grams

REVISIONS

LTR	DESCRIPTION	DATE	APPROVED
—	RELEASED FROM ENGINEERING	3/22/06	



NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
3. THIS PART IS RoHS 2002/95/EC COMPLIANT

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN
MILLIMETERS, TOLERANCES ARE ± 0.5 AND
ANGLES ARE $\pm 3^\circ$.

APPROVALS		DATE
DRAWN	TG	3/06
CHECKED	BR	3/06
APPROVED	EP	3/06

projects®
unlimited

Dayton , Ohio

INDICATOR

SIZE
A

DRAWING NO.

AI-4329-P-FP28-R

SCALE: N.T.S.

SHEET 1 OF 1