

Features

Unregulated Converter

- 1 : 1 Input Range
- 0.5W SMD Package
- Efficiency up to 80%
- Approved for Medical Applications
- 1kVDC and 3 kVDC Isolation Option
- Operating Temperature from -40°C to +100°C

ECONOLINE

DC/DC-Converter

with 3 year Warranty

RECOM

Specifications (measured at $T_A = 25^\circ\text{C}$, nominal input voltage, full load and after warm-up)

Part Number SMD	Input Voltage (VDC)	Output Voltage (VDC)	Output Current (mA)	Efficiency typ. (%)	Max Capacitive Load ^{(1)**}
R0.5S**-3.305*	3.3	5	100	80	1000µF
R0.5S**-3.312*	3.3	12	42	77	150µF
R0.5S**-3.315*	3.3	15	33	77	150µF
R0.5S**-0505*	5	5	100	72	1000µF
R0.5S**-0512*	5	12	42	77	150µF
R0.5S**-0515*	5	15	33	79	150µF
R0.5S**-1205*	12	5	100	74	1000µF
R0.5S**-1212*	12	12	42	75	150µF
R0.5S**-1215*	12	15	33	75	150µF
R0.5S**-2405*	24	5	100	75	1000µF
R0.5S**-2412*	24	12	42	77	150µF
R0.5S**-2415*	24	15	33	77	150µF
R0.5D**-3.305*	3.3	±5	±50	79	±470µF
R0.5D**-3.312*	3.3	±12	±21	76	±68µF
R0.5D**-3.315*	3.3	±15	±17	77	±68µF
R0.5D**-0505*	5	±5	±50	79	±470µF
R0.5D**-0512*	5	±12	±21	77	±68µF
R0.5D**-0515*	5	±15	±17	79	±68µF
R0.5D**-1205*	12	±5	±50	76	±470µF
R0.5D**-1212*	12	±12	±21	75	±68µF
R0.5D**-1215*	12	±15	±17	75	±68µF
R0.5D**-2405*	24	±5	±50	77	±470µF
R0.5D**-2412*	24	±12	±21	75	±68µF
R0.5D**-2415*	24	±15	±17	75	±68µF

*add Suffix "/H" for 3kVDC Isolation Voltage

*add Suffix "/P" for continuous short circuit protection

*add Suffix "-R" for tape & reel packing

For more details and dimensions of the tapes and reels see Application Notes

R0.5S**:

**without marking denotes 5 pins out of 8 fitted (includes „/H" option)

**with marking 8 denotes 8 pins out of 8 fitted („/H" option not available)

**with marking 12 denotes 10 pins out of 12 fitted (includes „/H" option)

R0.5D**:

**without marking denotes 6 pins out of 10 fitted (includes „/H" option)

**with marking 10 denotes 10 pins out of 10 fitted („/H" option not available)


**with marking 12 denotes 10 pins out of 12 fitted (includes „/H" option)

0.5 Watt SMD Isolated Single or Dual Output



R0.5S_D

Derating-Graph (Ambient Temperature)




Refer to Application Notes

Specifications (measured at $T_A = 25^\circ\text{C}$, nominal input voltage, full load and after warm-up)



Input Voltage Range		$\pm 10\%$ max.
Voltage set accuracy	100% Load/nominal Vin	-1% typ. / $\pm 5\%$ max.
Line Regulation	Low Line to High Line @ max. Load	1.2% typ.
Load Regulation	5V output	6% typ. / 15% max.
(10% to 100% Load)	12/15V output	5%typ. / 10% max.
Ripple & Noise @ 20MHz BW		50 mVp-p typ. / 100mVp-p max.
Efficiency at Full Load		70% min.
Operating Temperature		-40°C to $+100^\circ\text{C}$
Storage Temperature		-55°C to $+125^\circ\text{C}$
Isolation Test Voltage (Tested for 1 second)	R0.5S_R0.5D	1000VDC
	R0.5S_R0.5D/H	3000VDC
Isolation Capacitance		75pF max.
Isolation Resistance	Viso = 500V	10 G Ω min.
Humidity		95% max.
Operating Frequency	Vin (nom.)	20kHz min. / 50 kHz typ. / 90 kHz max.
Short-Circuit Protection		1 Second
MTBF	Using MIL-HDBK 217F ($+100^\circ\text{C}$)	1003×10^3 hours
	Using MIL-HDBK 217F ($+25^\circ\text{C}$)	3962×10^3 hours
<i>Detailed Information see Application Notes chapter „MTBF“</i>		
Weight	Single Types	1.0 g
	Dual Types	1.2 g

Typical Characteristics



R0.5S-3.3xx





R0.5S-05xx





R0.5S-12xx





R0.5S-24xx





R0.5D-3.3xx





R0.5D-05xx



R0.5D-12xx




R0.5D-24xx



Package Style and Pinning (mm)

5 PINS Single SMD Package

3rd angle projection



Footprint


Pin Connections

Pin #	Single	Dual
1	-Vin	-Vin
2	+Vin	+Vin
4	-Vout	Com.
5	+Vout	-Vout
7	No Pin	+Vout
8	NC	No Pin
10	No Pin	NC

NC= No Connection

UNIT: mm
TOL.: ± 0.25 mm

6 PINS Dual SMD Package




Footprint

Package Style and Pinning (mm)

8 PINS Single SMD Package

3rd angle
projection



Footprint


Pin Connections

Pin #	Single	Dual
1	-Vin	-Vin
2	+Vin	+Vin
4	-Vout	Com.
5	+Vout	-Vout
7	NC	+Vout
3, 6, 8	NC	NC
9, 10	No Pin	NC

NC= No Connection

UNIT: mm
TOL.: ± 0.25 mm

10 PINS Dual SMD Package



Footprint

Package Style and Pinning (mm)

12 PINS Dual SMD Package

