Old Company Name in Catalogs and Other Documents

On April 1st, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: http://www.renesas.com

April 1st, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (http://www.renesas.com)
Send any inquiries to http://www.renesas.com/inquiry.



Notice

- 1. All information included in this document is current as of the date this document is issued. Such information, however, is subject to change without any prior notice. Before purchasing or using any Renesas Electronics products listed herein, please confirm the latest product information with a Renesas Electronics sales office. Also, please pay regular and careful attention to additional and different information to be disclosed by Renesas Electronics such as that disclosed through our website.
- Renesas Electronics does not assume any liability for infringement of patents, copyrights, or other intellectual property rights
 of third parties by or arising from the use of Renesas Electronics products or technical information described in this document.
 No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights
 of Renesas Electronics or others.
- 3. You should not alter, modify, copy, or otherwise misappropriate any Renesas Electronics product, whether in whole or in part.
- 4. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation of these circuits, software, and information in the design of your equipment. Renesas Electronics assumes no responsibility for any losses incurred by you or third parties arising from the use of these circuits, software, or information.
- 5. When exporting the products or technology described in this document, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You should not use Renesas Electronics products or the technology described in this document for any purpose relating to military applications or use by the military, including but not limited to the development of weapons of mass destruction. Renesas Electronics products and technology may not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations.
- 6. Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.
- 7. Renesas Electronics products are classified according to the following three quality grades: "Standard", "High Quality", and "Specific". The recommended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below. You must check the quality grade of each Renesas Electronics product before using it in a particular application. You may not use any Renesas Electronics product for any application categorized as "Specific" without the prior written consent of Renesas Electronics. Further, you may not use any Renesas Electronics product for any application for which it is not intended without the prior written consent of Renesas Electronics. Renesas Electronics shall not be in any way liable for any damages or losses incurred by you or third parties arising from the use of any Renesas Electronics product for an application categorized as "Specific" or for which the product is not intended where you have failed to obtain the prior written consent of Renesas Electronics. The quality grade of each Renesas Electronics product is "Standard" unless otherwise expressly specified in a Renesas Electronics data sheets or data books, etc.

"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; and industrial robots.

"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control systems; anti-disaster systems; anti-crime systems; safety equipment; and medical equipment not specifically designed for life support.

"Specific": Aircraft; aerospace equipment; submersible repeaters; nuclear reactor control systems; medical equipment or systems for life support (e.g. artificial life support devices or systems), surgical implantations, or healthcare intervention (e.g. excision, etc.), and any other applications or purposes that pose a direct threat to human life.

- 8. You should use the Renesas Electronics products described in this document within the range specified by Renesas Electronics, especially with respect to the maximum rating, operating supply voltage range, movement power voltage range, heat radiation characteristics, installation and other product characteristics. Renesas Electronics shall have no liability for malfunctions or damages arising out of the use of Renesas Electronics products beyond such specified ranges.
- 9. Although Renesas Electronics endeavors to improve the quality and reliability of its products, semiconductor products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Further, Renesas Electronics products are not subject to radiation resistance design. Please be sure to implement safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of a Renesas Electronics product, such as safety design for hardware and software including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
- 10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. Please use Renesas Electronics products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. Renesas Electronics assumes no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
- 11. This document may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of Renesas Electronics
- 12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products, or if you have any other inquiries.
- (Note 1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its majority-owned subsidiaries.
- (Note 2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

78K series Product Letter

78K0/KC2

8-bit Microcontroller

Description

The 78K0/KC2 is a powerful 44/48-pin general-purpose device in the K_Line. Derived directly from the 78K0/KC1(+), its successful predecessor, the 78K0/KC2 is highly compatible with other K_Line microcontrollers. The 78K0/KC2 combines a wealth of peripherals with state-of-the-art Flash technology. Taking advantage of modern 0.15 µm process technology, it offers Flash memory in various sizes at almost the same price as Mask ROM devices.

Applications

The large number of on-chip peripherals makes the 78K0/KC2 an excellent choice for a variety of applications including industrial control, automotive systems (eg LIN slaves), alarm systems, white goods and communication equipment.

Features

- 8-bit 78K0 CPU core
- Hardwired instructions for bit manipulation, multiplication and division
- 20 MHz max. clock frequency (100 ns min. instruction cycle time)
- Two on-chip oscillators (8 MHz and 240 kHz)
- Optional external oscillators (up to 20 MHz, 32 KHz)
- Single-voltage Flash memory
- Secure self-programming
- E²PROM emulation
- Power-on clear (POC/POR) with RESET output*
- Low-voltage indicator (LVI)
- Window watchdog

- Dedicated 16x16→32 multiplier and 32/16→32 divider*
- 8-channel A/D converter with 10-bit resolution
- Advanced UART (highly flexible, supports LIN by hardware)
- Standard UART
- One 3-wire serial interface (SPI)
- Multimaster capable I2C interface
- Four 8-bit timers, one 16-bit timer
- 27/41* I/Os
- Operating voltage: 1.8 to 5.5 V
- Operating temperature: -40 to +125 °C*
- Package: 44-pin LQFP and 48-pin (FP)LQFP
- On-chip debug version available

* device dependent

Block Diagram

1 x 16-bit timer	44/48-pin QFP package 44-pin: LQFP (10x10 mm², 0.8 mm pin pitc	Interrupt control 7/8 external / 16 internal
4 x 8-bit timer	48-pin: LQFP (7x7 mm², 0.5 mm pin pitch	Power-on-reset, low-voltage indicator
2 x UART 1 LIN-capable	78K0 Core 16-bit operations (incl. 8x8 multiplication & 16/8 division)	A/D-converter 8 x 10-bit
1 x SPI	100 ns @ 20 MHz 1.8 - 5.5 V	Key return inputs
1 × 120		
1 x I ² C	16 Kbytes Flash*, 768 Bytes RAM: 78F0	511 Clock out / buzzer out (48-pin version only)
Window watchdog	24 Kbytes Flash*, 1 Kbyte RAM: 78F0	
	32 Kbytes Flash*, 1 Kbyte RAM: 78F0	513
Watch timer	48 Kbytes Flash*, 2 Kbytes RAM: 78F05	14**
	60 Kbytes Flash*, 3 Kbytes RAM: 78F05	Extended multiplier
Subclock oscillator 32 KHz	is in the second of the second	
2 x on-chip oscillator	OCD, 44-pin: 78F05	13D Voltage regulator
8 MHz, 240 kHz	OCD, 48-pin: 78F05	15D
Crystal/ceram. oscillator up to 20 MHz	* single voltage, self-progran ** only 48-pin version	nming 37/41 I/O lines



Ordering Information

Devices

Part number	Flash memory [Kbytes]	RAM [bytes]	Multiplier/ divider	On-chip debug interface	Packages
μPD78F0511	16	0.75	no	no	GA-8EU, GB-UES
μPD78F0512	24	1	no	no	GA-8EU, GB-UES
μPD78F0513	32	1	no	no	GA-8EU, GB-UES
μPD78F0513D	32	1	no	yes	GB-UES
μPD78F0514	48	2	yes	no	GA-8EU
μPD78F0515	60	3	yes	no	GA-8EU
μPD78F0515D	60	3	yes	yes	GA-8EU

Packaging: $GA-8EU = (FP)LQFP (48-pin, 7 x 7 mm^2, 0.5 mm pin pitch)$ $GB-UES = LQFP (44-pin, 10 x 10 mm^2, 0.8 mm pin pitch)$

Documentation

Doc Reference	Devices	Туре
U12326EJ	78K0 series	Instruction Manual
ZUD-CC-04-0126-E	78K0/KC2	Preliminary Product Information (PPI)
U17336EJ	78K0/KC2	User's Manual/Datasheet

For further information on NEC's 78K controllers visit our European website at www.ee.nec.de/78k

Contact

European Headquarters:

NEC Electronics (Europe) GmbH Arcadiastr. 10, 40472 Düsseldorf, Germany Tel. +49 211 65030 Fax +49 211 6503-1327

www.ee.nec.de

Offices in Europe:

www.ee.nec.de/europe

Distributors in Europe:

www.ee.nec.de/distributors

Offices world-wide:

www.ee.nec.de/global

© Published by NEC Electronics (Europe) GmbH

Printed in Germany, February 2005 Document No. U17426EE1V0PL00