

STRUCTURE SILICON MONOLITHIC INTEGRATED CIRCUIT

FUNCTION LOW NOISE DUAL OPERATIONAL AMPLIFIERS

PRODUCT SERIES **BA4558RF**  
**BA4558RFV**  
**BA4558RFVM**

FEATURES • Wide operating temperature range. ( $-40\sim+105[^{\circ}\text{C}]$ )  
 • Internal phase compensation type.

○ABSOLUTE MAXIMUM RATINGS( $T_a=25[^{\circ}\text{C}]$ )

| Parameter                       | Symbol  | Rating             | Unit               |
|---------------------------------|---------|--------------------|--------------------|
| Supply Voltage                  | VCC-VEE | +36                | V                  |
| Power dissipation               | Pd      | BA4558RF           | 780(*1) (*4)       |
|                                 |         | BA4558RFV          | 690(*2) (*4)       |
|                                 |         | BA4558RFVM         | 590(*3) (*4)       |
| Differential Input Voltage (*5) | Vid     | $\pm 36$           | V                  |
| Input Common-mode Voltage Range | Vicm    | (VEE-0.3) ~ VEE+36 | V                  |
| Operating Temperature           | Topr    | $-40\sim+105$      | $^{\circ}\text{C}$ |
| Storage Temperature Range       | Tstg    | $-55\sim+150$      | $^{\circ}\text{C}$ |
| Maximum junction Temperature    | Tjmax   | 150                | $^{\circ}\text{C}$ |

• This IC is not designed for protection against radioactive rays.

(\*1) To use at temperature above  $T_a=25[^{\circ}\text{C}]$  reduce  $6.3[\text{mW}]/[^{\circ}\text{C}]$ .

(\*2) To use at temperature above  $T_a=25[^{\circ}\text{C}]$  reduce  $5.6[\text{mW}]/[^{\circ}\text{C}]$ .

(\*3) To use at temperature above  $T_a=25[^{\circ}\text{C}]$  reduce  $4.8[\text{mW}]/[^{\circ}\text{C}]$ .

(\*4) Mounted on a glass epoxy PCB( $70[\text{mm}]\times 70[\text{mm}]\times 1.6[\text{mm}]$ ).

(\*5) The voltage difference between inverting input and non-inverting input is the differential input voltage. Then input terminal voltage is set to more than VEE.

○OPERATING CONDITION( $T_a=-40\sim+105[^{\circ}\text{C}]$ )

| Parameter      | Symbol | Rating                                                                  | Unit |
|----------------|--------|-------------------------------------------------------------------------|------|
| Supply Voltage | VCC    | $\pm 4.0\sim\pm 15.0$ (Split Supply)<br>$+8.0\sim+30.0$ (Single Supply) | V    |

Status of this document

The Japanese version of this document is the formal specification.

A customer may use this translation version only for a reference to help reading the formal version.

If there are any differences in translation version of this document formal version takes priority.

Application example

• ROHM cannot provide adequate confirmation of patents.

• The product described in this specification is designed to be used with ordinary electronic equipment or devices (such as audio-visual equipment, office-automation equipment, communications devices, electrical appliances, and electronic toys).

Should you intend to use this product with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.


• ROHM assumes no responsibility for use of any circuits described herein, conveys no license under any patent or other right, and makes no representations that the circuits are free from patent infringement.

## ○ELECTRICAL CHARACTERISTICS (unless otherwise specified VCC=+15[V], VEE=-15[V])


| Parameter                       | Symbol | Temperature Range | Guaranteed Limit |       |      | Unit   | Condition                                      |
|---------------------------------|--------|-------------------|------------------|-------|------|--------|------------------------------------------------|
|                                 |        |                   | Min.             | Typ.  | Max. |        |                                                |
| Input Offset Voltage (*6)       | Vio    | 25°C              | -                | 0.5   | 6    | mV     | VOUT=0[V]                                      |
|                                 |        | full range        | -                | -     | 7    |        |                                                |
| Input Offset Current (*6)       | Iio    | 25°C              | -                | 5     | 200  | nA     | VOUT=0[V]                                      |
|                                 |        | full range        | -                | -     | 200  |        |                                                |
| Input Bias Current (*6)         | Ib     | 25°C              | -                | 60    | 500  | nA     | VOUT=0[V]                                      |
|                                 |        | full range        | -                | -     | 800  |        |                                                |
| Supply Current                  | ICC    | 25°C              | -                | 3     | 6    | mA     | RL=∞ All Op-Amps, VIN+=0[V]                    |
|                                 |        | full range        | -                | -     | 6.5  |        |                                                |
| Maximum Output Voltage          | VOH    | 25°C              | ±10              | ±13   | -    | V      | RL≥2[kΩ]                                       |
|                                 |        | full range        | ±10              | -     | -    |        |                                                |
|                                 |        | 25°C              | ±12              | ±14   | -    |        | RL≥10[kΩ]                                      |
| Large Signal Voltage Gain       | AV     | 25°C              | 86               | 100   | -    | dB     | RL≥2[kΩ], VOUT=±10[V], VIN+=0[V]               |
|                                 |        | full range        | 83               | -     | -    |        |                                                |
| Input Common-mode Voltage Range | Vicm   | 25°C              | ±12              | ±14   | -    | V      | VOUT=±12[V]                                    |
|                                 |        | full range        | ±12              | -     | -    |        |                                                |
| Common-mode Rejection Ratio     | CMRR   | 25°C              | 70               | 90    | -    | dB     | VOUT=±12[V]                                    |
| Power Supply Rejection Ratio    | PSRR   | 25°C              | 76.5             | 90    | -    | dB     | RI≤10[kΩ]                                      |
| Channel Separation              | CS     | 25°C              | -                | 105   | -    | dB     | RI=100[Ω], f=1[kHz]                            |
| Slew Rate                       | SR     | 25°C              | -                | 1     | -    | V/μs   | AV=0[dB], RL=2[kΩ], CL=100[pF]                 |
| Maximum Frequency               | ft     | 25°C              | -                | 2     | -    | MHz    | RL=2[kΩ]                                       |
| Total Harmonic Distortion       | THD    | 25°C              | -                | 0.005 | -    | %      | AV=20[dB], RL=10[kΩ], VIN=0.05[Vrms], f=1[kHz] |
| Input Referred Noise Voltage    | Vn     | 25°C              | -                | 12    | -    | nV/√Hz | RS=100[Ω], Vi=0[V], f=1[kHz]                   |

(\*6) Absolute value.


## ○Physical Dimensions




BA4558RF (SOP8) (Unit:[mm])



BA4558RFV (SSOP-B8) (Unit:[mm])



BA4558RFVM (MSOP8) (Unit:[mm])



○Pin No. • Pin Name

| Pin No. | Pin Name |
|---------|----------|
| 1       | OUT1     |
| 2       | -IN1     |
| 3       | +IN1     |
| 4       | VEE      |
| 5       | +IN2     |
| 6       | -IN2     |
| 7       | OUT2     |
| 8       | VCC      |

F:SOP8 FV:SSOP-B8 FVM:MSOP8

○Application example

(1) Absolute maximum ratings

Absolute maximum ratings are the values which indicate the limits, within which the given voltage range can be safely charged to the terminal. However, it does not guarantee the circuit operation.

(2) The example of disabled circuit application

When there is a circuit not in use, it is recommended to make the non-inverting input terminal be the potential in the common-mode input voltage range like in Fig.1. Circuit operation is guaranteed within "Operating Conditions".




Fig.1 The example of disable circuit

(3) Applied voltage to the input terminal

For normal circuit operation of comparator, please input voltage for its input terminal within input common mode voltage  $VCC-1.5[V]$ . Then, regardless of power supply voltage,  $VEE+36[V]$  can be applied to input terminals without deterioration or destruction of its characteristics.

(4) Maximum output voltage

Because the output voltage range becomes narrow as the output current increases, design the application with margin by considering changes in electrical characteristics and temperature characteristics.

(5) Output short circuit

If short circuits occur between the output terminal and VCC terminal or between the output terminal and VEE terminal, excessive output current may flow and generate heat, causing destruction of the IC depending on the conditions. To prevent this, protection against short circuit is required by Connecting a resistor as shown in Fig.2.




Fig.2 The example of protection resistor

(6) Operating power supply (split power supply/single power supply)

The OP-Amp operates if a given level of voltage is applied between VCC and VEE. Therefore, the OP-Amp can be operated under single power supply or split power supply.

(7) Power dissipation(Pd)

If the IC is used under excessive power dissipation. An increase in the chip temperature will cause deterioration of the radical characteristics of IC.

For example, reduction of current capability. Take consideration of the effective power dissipation and thermal design with a sufficient margin. Pd is reference to the provided power dissipation curve.

(8) Short circuits between pins and incorrect mounting

Short circuits between pins and incorrect mounting when mounting the IC on a printed circuits board, take notice of the direction and positioning of the IC.

If IC is mounted erroneously, It may be damaged. Also, when a foreign object is inserted between output, between output and power supply or GND terminal which causes short circuit, the IC may be damaged.

- (9) Using under strong electromagnetic field  
Be careful when using the IC under strong electromagnetic field because it may malfunction.
- (10) Usage of IC  
When stress is applied to the IC through warp of the printed circuit board,  
The characteristics may fluctuate due to the piezo effect.  
Be careful of the warp of the printed circuit board.
- (11) Testing IC on the set board  
When testing IC on the set board, in cases where the capacitor is connected to the low impedance,  
make sure to discharge per fabrication because there is a possibility that IC may be damaged by stress.  
When removing IC from the set board, it is essential to cut supply voltage.  
As a countermeasure against the static electricity, observe proper grounding during fabrication process  
and take due care when carrying and storage it.
- (12) The IC destruction caused by capacitive load  
The transistors in circuits may be damaged when VCC terminal and VEE terminal is shorted with the charged  
output terminal capacitor.  
When IC is used as a comparator or as application circuits no constructed negative feed back,  
where oscillation is not activated by an output capacitor, the output capacitor must be kept below  
0.1[μF] in order to prevent the damage mentioned above.
- (13) The oscillation caused by capacitive load  
Designed negative feedback circuit using this IC, verify output oscillation caused by capacitive load.

### Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

#### About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.

Thank you for your accessing to ROHM product informations.  
More detail product informations and catalogs are available,  
please contact your nearest sales office.

Please contact our sales offices for details ;

|                         |                           |                            |
|-------------------------|---------------------------|----------------------------|
| U.S.A / San Diego       | TEL : +1(858)625-3630     | FAX : +1(858)625-3670      |
| Atlanta                 | TEL : +1(770)754-5972     | FAX : +1(770)754-0691      |
| Dallas                  | TEL : +1(972)312-8818     | FAX : +1(972)312-0330      |
| Germany / Dusseldorf    | TEL : +49(2154)9210       | FAX : +49(2154)921400      |
| United Kingdom / London | TEL : +44(1)908-282-666   | FAX : +44(1)908-282-528    |
| France / Paris          | TEL : +33(0)1 56 97 30 60 | FAX : +33(0) 1 56 97 30 80 |
| China / Hong Kong       | TEL : +852(2)740-6262     | FAX : +852(2)375-8971      |
| Shanghai                | TEL : +86(21)6279-2727    | FAX : +86(21)6247-2066     |
| Dalian                  | TEL : +86(411)8230-8549   | FAX : +86(411)8230-8537    |
| Beijing                 | TEL : +86(10)8525-2483    | FAX : +86(10)8525-2489     |
| Taiwan / Taipei         | TEL : +866(2)2500-6956    | FAX : +866(2)2503-2869     |
| Korea / Seoul           | TEL : +82(2)8182-700      | FAX : +82(2)8182-715       |
| Singapore               | TEL : +65-6332-2322       | FAX : +65-6332-5662        |
| Malaysia / Kuala Lumpur | TEL : +60(3)7958-8355     | FAX : +60(3)7958-8377      |
| Philippines / Manila    | TEL : +63(2)807-6872      | FAX : +63(2)809-1422       |
| Thailand / Bangkok      | TEL : +66(2)254-4890      | FAX : +66(2)256-6334       |

Japan /  
(Internal Sales)

|                                                   |                                                                                              |                        |
|---------------------------------------------------|----------------------------------------------------------------------------------------------|------------------------|
| Tokyo                                             | 2-1-1, Yaesu, Chuo-ku, Tokyo 104-0082                                                        |                        |
|                                                   | TEL : +81(3)5203-0321                                                                        | FAX : +81(3)5203-0300  |
| Yokohama                                          | 2-4-8, Shin Yokohama, Kohoku-ku, Yokohama, Kanagawa 222-8575                                 |                        |
|                                                   | TEL : +81(45)476-2131                                                                        | FAX : +81(45)476-2128  |
| Nagoya                                            | Dainagayo Building 9F 3-28-12, Meieki, Nakamura-ku, Nagoya, Aichi 450-0002                   |                        |
|                                                   | TEL : +81(52)581-8521                                                                        | FAX : +81(52)561-2173  |
| Kyoto                                             | 579-32 Higashi Shiokouji-cho, Karasuma Nishi-iru, Shiokoujidori, Shimogyo-ku, Kyoto 600-8216 |                        |
|                                                   | TEL : +81(75)311-2121                                                                        | FAX : +81(75)314-6559  |
| (Contact address for overseas customers in Japan) |                                                                                              |                        |
| Yokohama                                          | TEL : +81(45)476-9270                                                                        | FAX : +81(045)476-9271 |