

# SPECIFICATION

- Supplier : Samsung electro-mechanics
- Product : Thick - Film chip RESISTOR

- Samsung P/N: **RC0603F\*\*\*CS**
- Description : **0603, ±1%, (1Ω~1MΩ), 1/20W**

## A. Samsung Part Number

RC 0603 F \*\*\* CS  
① ② ③ ④ ⑤

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                        |                   |                   |                    |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------|--------------------|
| ① Code designation         | Samsung Thick - Film Chip Resistor                                                                                                                                                                                                                                                                                                                                                                                                     |                   |                   |                    |
| ② Dimension                | 0603 (mm code)                                                                                                                                                                                                                                                                                                                                                                                                                         | L : 0.6 ± 0.03 mm | W : 0.3 ± 0.03 mm | T : 0.23 ± 0.03 mm |
| ③ Resistances tolerance    | ±1 %                                                                                                                                                                                                                                                                                                                                                                                                                                   |                   |                   |                    |
| ④ Nominal resistance value | ※ 3digits · Left 2 digits : Resistance value, Right 1 digits : Exponential number of 10.<br>ex) 101 : $10 \times 10^1 = 10 \times 10 = 100\Omega$<br>※ 4digits · Left 3 digits : Resistance value, Right 1 digits : Exponential number of 10.<br>ex) 4222 : $422 \times 10^2 = 422 \times 100 = 42.2k\Omega$<br>Read alphabet "R" as decimal point      "000" : Jumper(0Ω)<br>ex) 3R7 : $3.7 = 3.7\Omega$ / 88R7 : $88.7 = 88.7\Omega$ |                   |                   |                    |
| ⑤ Packing code             | 7" Reel packaging                                                                                                                                                                                                                                                                                                                                                                                                                      |                   |                   |                    |

## B. Samsung Reliability Test and Judgement condition

|                                 | Judgement                                                                                                                                                                                                                                         |          | Test condition                                                                                                                                                                                                                                                      |                   |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
|                                 | Resistor                                                                                                                                                                                                                                          | Jumper   | Resistor                                                                                                                                                                                                                                                            | Jumper            |
| Direct Current Resistance       | Within the regulated resistance tolerance.                                                                                                                                                                                                        | 50mΩ Max | Voltage apply Within 5 sec                                                                                                                                                                                                                                          |                   |
| Short-time Overload             | Less than ±(1%+0.1Ω) of the initial value<br>No evidence of mechanical damage                                                                                                                                                                     | 50mΩ Max | Apply 2.5 times rated voltage for 5sec                                                                                                                                                                                                                              | Max Surge Current |
| Intermittent Overload           | Less than ±(3%+0.1Ω) of the initial value<br>No evidence of mechanical damage                                                                                                                                                                     | 50mΩ Max | 2.5 times of rated voltage.<br>1 sec On, 25 sec Off / 10,000cycles                                                                                                                                                                                                  | Max Surge Current |
| Dielectric Withstanding Voltage | No evidence of mechanical damage                                                                                                                                                                                                                  |          | Apply Voltage for 1minute<br>0603:50v                                                                                                                                                                                                                               |                   |
| Insulation Resistance           | Over 1,000MΩ                                                                                                                                                                                                                                      |          | 1005,1608:100v<br>Other: 500v                                                                                                                                                                                                                                       |                   |
| Temperature Characteristic      | ■ J-Grade<br>$1\Omega \leq R < 10\Omega$ : +300/-200ppm/°C<br>$10\Omega \leq R \leq 1M\Omega$ : ±100ppm/°C (0603±250ppm)<br>$1M\Omega < R \leq 10M\Omega$ : ±300ppm/°C<br>■ F-Grade<br>$10\Omega \leq R \leq 1M\Omega$ : ±100ppm/°C (0603±250ppm) |          | Test Temperature(°C) 20°C → -55°C / 20°C → 125°C<br>$T.C.R(ppm/^{\circ}C) = \frac{R - R_0}{R_0} \times \frac{1}{T - T_0} \times 10^6$ T <sub>0</sub> : 20 ± 2°C, R <sub>0</sub> : Resistance at T <sub>0</sub> (Ω)<br>T : Test temperature, R : Resistance at T (Ω) |                   |
| Solderability                   | Coverage: 95% ≤ each termination.                                                                                                                                                                                                                 |          | Solder Temp : 245°C<br>Dipping time : 3 sec                                                                                                                                                                                                                         |                   |

|                                         | Judgement                                                                                  |                  | Test condition                                                                                      |
|-----------------------------------------|--------------------------------------------------------------------------------------------|------------------|-----------------------------------------------------------------------------------------------------|
| <b>Bending test</b>                     | Less than $\pm(0.5\%+0.05\Omega)$ of the initial value<br>No evidence of mechanical damage | 50m $\Omega$ Max | 3mm of bending shall be applied for 5sec.                                                           |
| <b>Adhesive strength of termination</b> | No mechanical damage or sign of disconnection                                              |                  | Test strength : 5N<br>Test time: Applying pressure for 10seconds                                    |
| <b>Resistance to soldering heat</b>     | Less than $\pm(1\%+0.05\Omega)$ of the initial value<br>No evidence of mechanical damage   | 50m $\Omega$ Max | 260 $\pm$ 5 $^{\circ}$ C , 10 sec                                                                   |
| <b>Anti-Vibration test</b>              | Less than $\pm(1\%+0.05\Omega)$ of the initial value<br>No evidence of mechanical damage   | 50m $\Omega$ Max | Test amplitude : 1.5mm<br>Frequency 10Hz-55Hz-10Hz / 2hr in x,y,z direction.                        |
| <b>Temperature cycle</b>                | Less than $\pm(1\%+0.1\Omega)$ of the initial value<br>No evidence of mechanical damage    | 50m $\Omega$ Max | 100cycles, -55 $^{\circ}$ C/30min $\leftrightarrow$ 125 $^{\circ}$ C/30min<br>sweep time:5min       |
| <b>Load life</b>                        | Less than $\pm(3\%+0.1\Omega)$ of the initial value<br>No evidence of mechanical damage    | 50m $\Omega$ Max | Test voltage: rated voltage / 70 $\pm$ 2 $^{\circ}$ C<br>1,000hours(90min:On , 30min:Off)           |
| <b>Low Temp. Exposure</b>               | Less than $\pm(3\%+0.1\Omega)$ of the initial value<br>No evidence of mechanical damage    | 50m $\Omega$ Max | Dwell in -55 $^{\circ}$ C chamber without loading for 1,000hours                                    |
| <b>High Temp Exposure</b>               | Less than $\pm(3\%+0.1\Omega)$ of the initial value<br>No evidence of mechanical damage    | 50m $\Omega$ Max | Dwell in 125 $^{\circ}$ C or 155 $^{\circ}$ C chamber without loading for 1,000hours                |
| <b>Moisture Resistance</b>              | Less than $\pm(3\%+0.1\Omega)$ of the initial value<br>No evidence of mechanical damage    | 50m $\Omega$ Max | Test voltage: rated voltage / 40 $\pm$ 2 $^{\circ}$ C<br>1,000hours(90min:On,30min:Off) / 90~95% RH |

### C. Recommended Soldering method :

Reflow ( Reflow Peak Temperature : 260 $\pm$ 0/-5  $^{\circ}$ C , 10sec. Max )

\* For the more detail Specification, Please refer to the samsung chip RESISTOR catalogue.