




(1,27 mm) .050"

TFM, TFML SERIES



# SMT & THROUGH-HOLE HEADER

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?TFM](http://www.samtec.com?TFM) or [www.samtec.com?TFML](http://www.samtec.com?TFML)

### Insulator Material:

Black Liquid Crystal Polymer

### Terminal Material:

Phosphor Bronze

### Plating:

Au or Sn over 50µ" (1,27 µm) Ni

### Current Rating (TFM/SFML):

3.2 A per pin

(1 pin powered per row)

### Voltage Rating:

250 VAC mated with SFM

### Operating Temp Range:

-55°C to +125°C

RoHS Compliant: Yes

### Processing:

Lead-Free Solderable: Yes

### SMT Lead Coplanarity:


(0,10 mm) .004" max (05-25)

(0,15 mm) .006" max (30-50)

**TFM Mates with:**  
SFM, SFMC, SFSD

**TFML Mates with:**  
SFML

**TFM-DH Mates with:**  
SFM (-DH), SFMC,  
SFSDX (-S, -D, -SR, -DR)




Shrouded body  
for blind mating


(1,27 mm x 1,27 mm)  
.050" x .050"  
micro pitch

Surface mount or  
Through-hole tails

## APPLICATIONS



TFM-DH to SFM-DH SHOWN



TFM to SFM-SH SHOWN

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



## MATED HEIGHT

| LEAD STYLE |     | MATED HEIGHT* |
|------------|-----|---------------|
| TFM        | SFM |               |
| -02        |     | (6,35) .250   |
| -12        | -02 | (8,13) .320   |
| -22        |     | (9,91) .390   |
| -32        |     | (11,81) .465  |

| LEAD STYLE |     | MATED HEIGHT* |
|------------|-----|---------------|
| TFM        | SFM |               |
| -01        |     | (5,97) .235   |
| -03        |     | (5,97) .235   |
| -11        | -01 | (7,75) .305   |
| -13        |     | (7,75) .305   |
| -21        |     | (9,53) .375   |
| -23        |     | (9,53) .375   |
| -31        |     | (11,43) .450  |

\*Processing conditions will affect mated height.

## OTHER SOLUTIONS

See TFC Series for lower cost plating options.

**Note:** Some sizes, styles and options are non-standard, non-returnable.

## TYPE STRIP

1

## NO. PINS PER ROW

03, 04, 06, 08  
(TFM & -01 only)

05, 07, 10, 15, 20,  
25, 30, 35, 40, 45, 50  
(Standard Sizes)

## LEAD STYLE

Specify  
LEAD STYLE  
from chart

## PLATING OPTION


-L  
= 15µ" (0,38 µm)  
Gold on post,  
Matte Tin on tail  
(Call Samtec for  
E.L.P. plating option)

TFM  
= Standard


TFML  
= Locking  
(-01 & -02  
lead style only)

| LEAD STYLE (T/H) | B            | C           |
|------------------|--------------|-------------|
| -01              | (5,59) .220  | (1,97) .078 |
| -03*             | (5,59) .220  | (2,77) .109 |
| -11*             | (7,37) .290  | (1,97) .078 |
| -13*             | (7,37) .290  | (2,77) .109 |
| -21*             | (9,14) .360  | (1,97) .078 |
| -23*             | (9,14) .360  | (2,77) .109 |
| -31*             | (11,05) .435 | (1,97) .078 |


\* N/A with 07 or -S row option



SINGLE ROW




DOUBLE ROW




THROUGH-HOLE SURFACE MOUNT

| LEAD STYLE (SMT) | A            |
|------------------|--------------|
| -02              | (5,72) .225  |
| -12*             | (7,49) .295  |
| -22*             | (9,27) .365  |
| -32*             | (11,18) .440 |


\* N/A with 07, -DH or -S row option



-A (SMT or TH)



-LC (SMT or TH)





-WT (-01 &amp; -02 ONLY)

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC NORTHERN CALIFORNIA • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329  
SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0  
SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292  
SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766  
SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683



## ROW OPTION

### -S



= Single Row  
(TFM only)

### -D

= Double Row

### -DH

= Double Horizontal  
(TFM lead style -02 only)  
(05 thru 50 positions only)  
(-WT standard; -TR option only available)



(-D, -01 & -02 ONLY)

Specify only -RA, -RE1 or -RE2

### -RA



= Right Angle  
(Lead style -01 only)

### -RE1

= Right Angle Elevated for (1,58 mm) .062" PCB  
(Requires TFM lead style -01, -D row and -WT)

### -RE2

= Right Angle Elevated for (2,36 mm) .093" PCB  
(Requires TFM lead style -01, -D row and -WT)



## OPTION

Specify only -A, -LC, -DS or -WT  
Not available with -RA, -RE1 and -RE2 unless otherwise noted.

### -A

= Alignment Pin

### -LC

= Locking Clip  
(Manual Placement required)

### -DS

= Dual Screw Down for  
(1,60 mm) .062" PCB  
(05, 07, 10, 15, 20, 25, 30, 35, 40 positions only)  
(TFM lead styles -01 and -02 only)  
(Requires -D row option)  
(Mates with SFM-DS option and SFSD/SFSDT -SS and -DS option only)

### -WT

= Weld Tab  
(TFM lead styles -01 and -02 only)  
(Required callout for -RE1 & -RE2)  
(Standard with -DH)  
(Mates to SFSS/SFSD -SR and -DR option only)  
(05, 07, 10, 15, 20, 25, 30, 35, 40, 45, 50 positions only)

SMT lead styles only  
Specify only -K or -P

### -K

= Polyimide Film Pick & Place Pad

### -P

= Plastic Pick & Place Pad  
(5 positions minimum)

Specify -TR last

### -TR

= Tape & Reel  
(Not available with -DS)

## ALSO AVAILABLE (MOQ Required)

- Solder nail option
- Other sizes
- Other platings
- Contact Samtec.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC NORTHERN CALIFORNIA • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329  
SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0  
SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292  
SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766  
SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683