

fuse GLDII 500V, super quick acting



See below:
[Approvals and Compliances](#)

Description

- Characteristic gR
- According to IEC 269
- According VDE 0636
- Protection of semiconductors
- Time-current characteristic on request
- Cut-off current characteristic on request

Technical Data

Rated Current In	2- 25A
Rated Voltage	500 VAC
Breaking Capacity	50 kA
Rated Power Operating Frequency fe	50 Hz

Basic Design

Insulator	Ceramic
Metal components	Brass

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

All Variants

Rated current	Style	Power Loss	Order Number	E-No
[A]	[Compact]	[W]		
2	-	-	0034.1101	800220209
4	-	-	0034.1102	800220409
6	-	-	0034.1103	800220609
10	-	-	0034.1104	800221009
16	-	-	0034.1105	800221609
20	-	-	0034.1106	800222009
25	-	-	0034.1107	800222509

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging Unit 5 Pcs