



## STP16DP05

### Low voltage 16-bit constant current LED sink driver with outputs error detection

#### Features

- Low voltage power supply down to 3 V
- 16 constant current output channels
- Adjustable output current through external resistor
- Short and open output error detection
- Serial data IN/Parallel data OUT
- 3.3 V micro driver-able
- Output current: 5-100 mA
- 30 MHz clock frequency
- Available in high thermal efficiency TSSOP exposed pad
- ESD protection 2.5 kV HBM, 200 V MM


#### Description

The STP16DP05 is a monolithic, low voltage, low current power 16-bit shift register designed for LED panel displays. The device contains a 16-bit serial-in, parallel-out shift register that feeds a 16-bit D-type storage register. In the output stage, sixteen regulated current sources were designed to provide 5-100 mA constant current to drive the LEDs.

The STP16DP05 features open and short LED detections on the outputs. The STP16DP05 is backward compatible with STP16C/L596. The detection circuit checks 3 different conditions that can occur on the output line: short to GND, short to  $V_O$  or open line.

**Table 1. Device summary**

| Order codes   | Package                             | Packaging           |
|---------------|-------------------------------------|---------------------|
| STP16DP05MTR  | SO-24 (tape and reel)               | 1000 parts per reel |
| STP16DP05TTR  | TSSOP24 (tape and reel)             | 2500 parts per reel |
| STP16DP05XTTR | TSSOP24 exposed pad (tape and reel) | 2500 parts per reel |
| STP16DP05PTR  | QSOP-24                             | 2500 parts per reel |



The data detection results are loaded in the shift register and shifted out via the serial line output.

The detection functionality is implemented without increasing the pin count number, through a secondary function of the output enable and latch pin (DM1 and DM2 respectively), a dedicated logic sequence allows the device to enter or leave from detection mode. Through an external resistor, users can adjust the STP16DP05 output current, controlling in this way the light intensity of LEDs, in addition, user can adjust LED's brightness intensity from 0% to 100% via  $\overline{OE}/DM2$  pin.

The STP16DP05 guarantees a 20 V output driving capability, allowing users to connect more LEDs in series. The high clock frequency, 30 MHz, makes the device suitable for high data rate transmission. The 3.3 V voltage supply is well useful for applications that interface any 3.3V micro. Compared with a standard TSSOP package, the TSSOP exposed pad increases heat dissipation capability by a 2.5 factor.

# Contents

|          |                                         |           |
|----------|-----------------------------------------|-----------|
| <b>1</b> | <b>Summary description</b>              | <b>3</b>  |
| 1.1      | Pin connection and description          | 3         |
| <b>2</b> | <b>Electrical ratings</b>               | <b>4</b>  |
| 2.1      | Absolute maximum ratings                | 4         |
| 2.2      | Thermal data                            | 4         |
| 2.3      | Recommended operating conditions        | 5         |
| <b>3</b> | <b>Electrical characteristics</b>       | <b>6</b>  |
| <b>4</b> | <b>Equivalent circuit and outputs</b>   | <b>8</b>  |
| <b>5</b> | <b>Timing diagrams</b>                  | <b>10</b> |
| <b>6</b> | <b>Typical characteristics</b>          | <b>13</b> |
| <b>7</b> | <b>Detection mode functionality</b>     | <b>16</b> |
| 7.1      | Phase one: “entering in detection mode” | 16        |
| 7.2      | Phase two: “error detection”            | 17        |
| 7.3      | Phase three: “resuming to normal mode”  | 19        |
| 7.4      | Error detection conditions              | 19        |
| <b>8</b> | <b>Package mechanical data</b>          | <b>22</b> |
| <b>9</b> | <b>Revision history</b>                 | <b>30</b> |


# 1 Summary description

**Table 2. Typical current accuracy**

| Output voltage | Current accuracy |             | Output current | V <sub>DD</sub> | Temperature |
|----------------|------------------|-------------|----------------|-----------------|-------------|
|                | Between bits     | Between ICs |                |                 |             |
| ≥ 1.3 V        | ±1.5%            | ±5%         | 20 to 100 mA   | 3.3 V to 5 V    | 25 °C       |

## 1.1 Pin connection and description

**Figure 1. Pin connection**



**Note:** The exposed pad should be electrically connected to a metal land electrically isolated or connected to ground

**Table 3. Pin description**

| Pin n° | Symbol                     | Name and function                                                                      |
|--------|----------------------------|----------------------------------------------------------------------------------------|
| 1      | GND                        | Ground terminal                                                                        |
| 2      | SDI                        | Serial data input terminal                                                             |
| 3      | CLK                        | Clock input terminal                                                                   |
| 4      | LE-DM1                     | Latch input terminal - detect mode 1 (see operation principle)                         |
| 5-20   | OUT 0-15                   | Output terminal                                                                        |
| 21     | $\overline{\text{OE-DM2}}$ | Input terminal of output enable (active low) - detect mode 1 (see operation principle) |
| 22     | SDO                        | Serial data out terminal                                                               |
| 23     | R-EXT                      | Input terminal of an external resistor for constant current programming                |
| 24     | V <sub>DD</sub>            | Supply voltage terminal                                                                |

## 2 Electrical ratings

### 2.1 Absolute maximum ratings

Stressing the device above the rating listed in the “absolute maximum ratings” table may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those indicated in the operating sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

**Table 4. Absolute maximum ratings**

| Symbol    | Parameter            | Value            | Unit |
|-----------|----------------------|------------------|------|
| $V_{DD}$  | Supply voltage       | 0 to 7           | V    |
| $V_O$     | Output voltage       | -0.5 to 20       | V    |
| $I_O$     | Output current       | 100              | mA   |
| $V_I$     | Input voltage        | -0.4 to $V_{DD}$ | V    |
| $I_{GND}$ | GND terminal current | 1600             | mA   |
| $f_{CLK}$ | Clock frequency      | 50               | MHz  |

### 2.2 Thermal data

**Table 5. Thermal data**

| Symbol     | Parameter                        |                                       | Value       | Unit |
|------------|----------------------------------|---------------------------------------|-------------|------|
| $T_{OPR}$  | Operating temperature range      |                                       | -40 to +125 | °C   |
| $T_{STG}$  | Storage temperature range        |                                       | -55 to +150 | °C   |
| $R_{thJC}$ | Thermal resistance junction-case | SO-24                                 | 42.7        | °C/W |
|            |                                  | TSSOP24                               | 55          | °C/W |
|            |                                  | TSSOP24 <sup>(1)</sup><br>exposed pad | 37.5        | °C/W |
|            |                                  | QSOP-24                               | 55          | °C/W |

1. The exposed pad should be soldered directly to the PCB to realize the thermal benefits.

## 2.3 Recommended operating conditions

**Table 6. Recommended operating conditions**

| Symbol         | Parameter                                 | Test conditions                            | Min.        | Typ. | Max.         | Unit |
|----------------|-------------------------------------------|--------------------------------------------|-------------|------|--------------|------|
| $V_{DD}$       | Supply voltage                            |                                            | 3.0         | -    | 5.5          | V    |
| $V_O$          | Output voltage                            |                                            |             | -    | 20           | V    |
| $I_O$          | Output current                            | OUTn                                       | 5           | -    | 100          | mA   |
| $I_{OH}$       | Output current                            | SERIAL-OUT                                 |             | -    | +1           | mA   |
| $I_{OL}$       | Output current                            | SERIAL-OUT                                 |             | -    | -1           | mA   |
| $V_{IH}$       | Input voltage                             |                                            | $0.7V_{DD}$ | -    | $V_{DD}+0.3$ | V    |
| $V_{IL}$       | Input voltage                             |                                            | -0.3        | -    | $0.3V_{DD}$  | V    |
| $t_{wLAT}$     | LE\DM1 pulse width                        | $V_{DD} = 3.0 \text{ V to } 5.0 \text{ V}$ | 6           | -    |              | ns   |
| $t_{wCLK}$     | CLK pulse width                           |                                            | 8           | -    |              | ns   |
| $t_{wEN}$      | $\overline{OE}\backslash DM2$ pulse width |                                            | 100         | -    |              | ns   |
| $t_{SETUP(D)}$ | Setup time for DATA                       |                                            | 10          | -    |              | ns   |
| $t_{HOLD(D)}$  | Hold time for DATA                        |                                            | 5           | -    |              | ns   |
| $t_{SETUP(L)}$ | Setup time for LATCH                      |                                            | 10          | -    |              | ns   |
| $f_{CLK}$      | Clock frequency                           | Cascade operation <sup>(1)</sup>           |             | -    | 30           | MHz  |

1. If the device is connected in cascade, it may not be possible achieve the maximum data transfer. Please consider the timings carefully.

### 3 Electrical characteristics

$V_{DD} = 3.3 \text{ V to } 5 \text{ V}$ ,  $T = 25 \text{ }^{\circ}\text{C}$ , unless otherwise specified

**Table 7. Electrical characteristics**

| Symbol           | Parameter                                        | Test conditions                                         | Min.                               | Typ.      | Max.        | Unit               |
|------------------|--------------------------------------------------|---------------------------------------------------------|------------------------------------|-----------|-------------|--------------------|
| $V_{IH}$         | Input voltage high level                         |                                                         | $0.7V_{DD}$                        |           | $V_{DD}$    | V                  |
| $V_{IL}$         | Input voltage low level                          |                                                         | GND                                |           | $0.3V_{DD}$ | V                  |
| $I_{OH}$         | Output leakage current                           | $V_{OH} = 20 \text{ V}$                                 |                                    |           | 1           | $\mu\text{A}$      |
| $V_{OL}$         | Output voltage (Serial-OUT)                      | $I_{OL} = 1 \text{ mA}$                                 |                                    |           | 0.4         | V                  |
| $V_{OH}$         | Output voltage (Serial-OUT)                      | $I_{OH} = -1 \text{ mA}$                                | $V_{OH} - V_{DD} = -0.4 \text{ V}$ |           |             | V                  |
| $I_{OL1}$        | Output current                                   | $V_O = 0.3 \text{ V}$ , $R_{ext} = 3.9 \text{ k}\Omega$ | 4.25                               | 5         | 5.75        | mA                 |
| $I_{OL2}$        |                                                  | $V_O = 0.3 \text{ V}$ , $R_{ext} = 970 \Omega$          | 19                                 | 20        | 21          |                    |
| $I_{OL3}$        |                                                  | $V_O = 1.3 \text{ V}$ , $R_{ext} = 190 \Omega$          | 96                                 | 100       | 104         |                    |
| $\Delta I_{OL1}$ | Output current error between bit (all output ON) | $V_O = 0.3 \text{ V}$ , $R_{EXT} = 3.9 \text{ k}\Omega$ |                                    | $\pm 5$   | $\pm 8$     | %                  |
| $\Delta I_{OL2}$ |                                                  | $V_O = 0.3 \text{ V}$ , $R_{EXT} = 970 \Omega$          |                                    | $\pm 1.5$ | $\pm 3$     |                    |
| $\Delta I_{OL3}$ |                                                  | $V_O = 1.3 \text{ V}$ , $R_{EXT} = 190 \Omega$          |                                    | $\pm 1.2$ | $\pm 3$     |                    |
| $R_{SIN(up)}$    | Pull-up resistor                                 |                                                         | 150                                | 300       | 600         | $\text{K}\Omega$   |
| $R_{SIN(down)}$  | Pull-down resistor                               |                                                         | 100                                | 200       | 400         | $\text{K}\Omega$   |
| $I_{DD(OFF1)}$   | Supply current (OFF)                             | $R_{EXT} = 970$<br>OUT 0 to 15 = OFF                    |                                    | 5         | 6           | mA                 |
| $I_{DD(OFF2)}$   |                                                  | $R_{EXT} = 240$<br>OUT 0 to 15 = OFF                    |                                    | 13        | 14          |                    |
| $I_{DD(ON1)}$    | Supply current (ON)                              | $R_{EXT} = 970$<br>OUT 0 to 15 = ON                     |                                    | 6         | 7           |                    |
| $I_{DD(ON2)}$    |                                                  | $R_{EXT} = 240$<br>OUT 0 to 15 = ON                     |                                    | 13.5      | 14.5        |                    |
| Thermal          | Thermal protection <sup>(1)</sup>                |                                                         |                                    | 170       |             | $^{\circ}\text{C}$ |

1. Guaranteed by design (not tested)  
The thermal protection switches OFF only the outputs current

$V_{DD} = 5\text{ V}$ ,  $T = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

**Table 8. Switching characteristics**

| Symbol            | Parameter                                                                   | Test conditions                                                                                                 |                                                                           | Min.                    | Typ. | Max. | Unit |    |
|-------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------|------|------|------|----|
| t <sub>PLH1</sub> | Propagation delay time,<br>CLK-OUT <sub>n</sub> , LE\DM1 = H,<br>OE\DM2 = L | V <sub>IH</sub> = V <sub>DD</sub><br>V <sub>IL</sub> = GND<br>I <sub>O</sub> = 20 mA<br>R <sub>EXT</sub> = 1 KΩ | C <sub>L</sub> = 10 pF<br>V <sub>L</sub> = 3.0 V<br>R <sub>L</sub> = 60 Ω | V <sub>DD</sub> = 3.3 V | -    | 40   | 65   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 20   | 30   |    |
| t <sub>PLH2</sub> | Propagation delay time,<br>LE\DM1 -OUT <sub>n</sub> ,<br>OE\DM2 = L         |                                                                                                                 |                                                                           | V <sub>DD</sub> = 3.3 V | -    | 51   | 77   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 32   | 47   |    |
| t <sub>PLH3</sub> | Propagation delay time,<br>OE\DM2-OUT <sub>n</sub> ,<br>LE\DM1 = H          |                                                                                                                 |                                                                           | V <sub>DD</sub> = 3.3 V | -    | 49   | 77   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 27   | 41   |    |
| t <sub>PLH</sub>  | Propagation delay time,<br>CLK-SDO                                          |                                                                                                                 |                                                                           | V <sub>DD</sub> = 3.3 V | -    | 21.5 | 32   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 14.5 | 21.5 |    |
| t <sub>PHL1</sub> | Propagation delay time,<br>CLK-OUT <sub>n</sub> , LE\DM1 = H,<br>OE\DM2 = L |                                                                                                                 |                                                                           | V <sub>DD</sub> = 3.3 V | -    | 15   | 25   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 11   | 14.5 |    |
| t <sub>PHL2</sub> | Propagation delay time,<br>LE\DM1 -OUT <sub>n</sub> ,<br>OE\DM2 = L         |                                                                                                                 |                                                                           | V <sub>DD</sub> = 3.3 V | -    | 13   | 20   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 9    | 12.5 |    |
| t <sub>PHL3</sub> | Propagation delay time,<br>OE\DM2-OUT <sub>n</sub> ,<br>LE\DM1 = H          |                                                                                                                 |                                                                           | V <sub>DD</sub> = 3.3 V | -    | 11.5 | 18   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 8.5  | 12   |    |
| t <sub>PHL</sub>  | Propagation delay time,<br>CLK-SDO                                          |                                                                                                                 |                                                                           | V <sub>DD</sub> = 3.3 V | -    | 25.5 | 38   | ns |
|                   |                                                                             |                                                                                                                 |                                                                           | V <sub>DD</sub> = 5 V   | -    | 17.5 | 25   |    |
| t <sub>ON</sub>   | Output rise time<br>10~90% of voltage<br>waveform                           | V <sub>DD</sub> = 3.3 V                                                                                         | -                                                                         | 34                      | 53.5 | ns   |      |    |
|                   |                                                                             | V <sub>DD</sub> = 5 V                                                                                           | -                                                                         | 12.5                    | 18.5 |      |      |    |
| t <sub>OFF</sub>  | Output fall time<br>90~10% of voltage<br>waveform                           | V <sub>DD</sub> = 3.3 V                                                                                         | -                                                                         | 5.5                     | 8.5  | ns   |      |    |
|                   |                                                                             | V <sub>DD</sub> = 5 V                                                                                           | -                                                                         | 4.5                     | 6.5  |      |      |    |
| t <sub>r</sub>    | CLK rise time <sup>(1)</sup>                                                |                                                                                                                 |                                                                           | -                       |      | 5000 | ns   |    |
| t <sub>f</sub>    | CLK fall time <sup>(1)</sup>                                                |                                                                                                                 |                                                                           | -                       |      | 5000 | ns   |    |

1. In order to achieve high cascade data transfer, please consider  $t_r/t_f$  timings carefully.

# 4      Equivalent circuit and outputs

Figure 2.     $\overline{\text{OE}}\backslash\text{DM2}$  terminal




Figure 3.     $\text{LE}\backslash\text{DM1}$  terminal




Figure 4.    CLK, SDI terminal




Figure 5. SDO terminal





Figure 6. Block diagram




## 5 Timing diagrams

**Table 9. Truth table**

| CLOCK                                                                             | LE\DM1 | OE\DM2 | SERIAL-IN | OUT0 ..... OUT7 ..... OUT15      | SDO     |
|-----------------------------------------------------------------------------------|--------|--------|-----------|----------------------------------|---------|
|  | H      | L      | Dn        | Dn ..... Dn - 7 ..... Dn -15     | Dn - 15 |
|  | L      | L      | Dn + 1    | No change                        | Dn - 14 |
|  | H      | L      | Dn + 2    | Dn + 2 ..... Dn - 5 ..... Dn -13 | Dn - 13 |
|  | X      | L      | Dn + 3    | Dn + 2 ..... Dn - 5 ..... Dn -13 | Dn - 13 |
|  | X      | H      | Dn + 3    | OFF                              | Dn - 13 |

*Note:*  $OUTn = ON$  when  $Dn = H$   $OUTn = OFF$  when  $Dn = L$

**Figure 7. Timing diagram**



- Note:*
- 1 Latch and output enable are level sensitive and ARE NOT synchronized with rising-or-falling edge of CALK signal.
  - 2 When LE terminal is low level, the latch circuits hold previous set of data
  - 3 When LE terminal is at high level, the latch circuits refresh new set of data from SDI chain.
  - 4 When OE terminal is at low level, the output terminals - Out0 to Out15 respond to data in the latch circuits, either '1' for ON or '0' for OFF
  - 5 When OE terminal is at high level, all output terminals will be switched OFF.


**Figure 8. Clock, serial-in, serial-out**

Figure 9. Clock, serial-in, latch, enable, outputs





Figure 10. Outputs



## 6 Typical characteristics

Figure 11. Output current- $R_{EXT}$  resistor




Table 10. Output current- $R_{EXT}$  resistor

| $R_{ext} (\Omega)$ | Output current (mA) |
|--------------------|---------------------|
| 976                | 20                  |
| 780                | 25                  |
| 652                | 30                  |
| 560                | 35                  |
| 488                | 40                  |
| 433                | 45                  |
| 389                | 50                  |
| 354                | 55                  |
| 325                | 60                  |
| 300                | 65                  |
| 278                | 70                  |
| 259                | 75                  |
| 241                | 80                  |
| 229                | 85                  |
| 215                | 90                  |

Conditions:  
Temperature = 25 °C,  $V_{DD}$  = 3.3 V; 5.0 V,  $I_{SET}$  = 3 mA; 5 mA; 10 mA; 20 mA; 50 mA; 80 mA.

Figure 12.  $I_{SET}$  vs drop out voltage ( $V_{drop}$ )




Table 11.  $I_{SET}$  vs drop out voltage ( $V_{drop}$ )

| $I_{out}$ (mA) | Avg @ 3.0 V | Avg @ 5.0 V |
|----------------|-------------|-------------|
| 3              | 19.33       | 22.66       |
| 5              | 36.67       | 40.33       |
| 10             | 77.33       | 80          |
| 20             | 158.67      | 157.33      |
| 50             | 406         | 406         |
| 80             | 692         | 668         |

Figure 13.  $I_{DD}$  ON/OFF





Figure 14. Power dissipation vs temperature package



Note: The exposed pad should be soldered to the PBC to realize the thermal benefits.

# 7 Detection mode functionality


## 7.1 Phase one: “entering in detection mode”

From the “normal mode” condition the device can switch to the “error mode” by a logic sequence on the  $\overline{OE/DM2}$  and LE/DM1 pins as showed in the following table and diagram:

Table 12. Entering in detection truth table

| CLK                 | 1° | 2° | 3° | 4° | 5° |
|---------------------|----|----|----|----|----|
| $\overline{OE/DM2}$ | H  | L  | H  | H  | H  |
| LE/DM1              | L  | L  | L  | H  | L  |

Figure 15. Entering in detection timing diagram




After these five CLK cycles the device goes into the “error detection mode” and at the 6<sup>th</sup> rise front of CLK the SDI data are ready for the sampling.

## 7.2 Phase two: “error detection”

The 16 data bits must be set “1” in order to set ON all the outputs during the detection. The data are latched by LE/DM1 and after that the outputs are ready for the detection process. When the micro controller switches the  $\overline{OE/DM2}$  to LOW, the device drives the LEDs in order to analyze if an OPEN or SHORT condition has occurred.


**Figure 16. Detection diagram**



The LEDs status will be detected at least in 1 microsecond and after this time the microcontroller sets  $\overline{OE/DM2}$  in HIGH state and the output data detection result will go to the microprocessor via SDO.

Detection mode and normal mode use both the same format data. As soon as all the detection data bits are available on the serial line, the device may go back to normal mode of operation. To re-detect the status the device must go back in normal mode and re-entering in error detection mode.

Figure 17. Timing example for open and/or short detection



### 7.3 Phase three: “resuming to normal mode”

The sequence for re-entering in normal mode is showed in the following table and diagram:

**Figure 18. Resuming to normal mode timing diagram**

| CLK                        | 1° | 2° | 3° | 4° | 5° |
|----------------------------|----|----|----|----|----|
| $\overline{\text{OE/DM2}}$ | H  | L  | H  | H  | H  |
| LE/DM1                     | L  | L  | L  | L  | L  |

*Note:* For proper device operation the “Entering in detection” sequence must be follow by a “resume mode” sequence, it is not possible to insert consecutive equal sequence.

### 7.4 Error detection conditions

$V_{DD} = 3.3$  to 5 V temperature range -40 to 125 °C

**Table 13. Detection conditions**

|                      |                                           |                                            |                   |                                            |
|----------------------|-------------------------------------------|--------------------------------------------|-------------------|--------------------------------------------|
| <b>SW-1 or SW-3b</b> | Open line or output short to GND detected | $\Rightarrow I_{ODEC} \leq 0.5 \times I_O$ | No error detected | $\Rightarrow I_{ODEC} \geq 0.5 \times I_O$ |
| <b>SW-2 or SW-3a</b> | Short on LED or short to V-LED detected   | $\Rightarrow V_O \geq 2.4 \text{ V}$       | No error detected | $\Rightarrow V_O \leq 2.2 \text{ V}$       |

*Note:* Where:  $I_O$  = the output current programmed by the  $R_{EXT}$ ,  $I_{ODEC}$  = the detected output current in detection mode

Figure 19. Detection circuit





Figure 20. Error detection sequence



## 8 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK<sup>®</sup> packages, depending on their level of environmental compliance. ECOPACK<sup>®</sup> specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK<sup>®</sup> is an ST trademark

**Table 14. QSOP-24 mechanical data**

| Dim. | mm.   |       |      | inch  |       |       |
|------|-------|-------|------|-------|-------|-------|
|      | Min.  | Typ.  | Max. | Min.  | Typ.  | Max.  |
| A    | 1.54  | 1.62  | 1.73 | 0.061 | 0.064 | 0.068 |
| A1   | 0.1   | 0.15  | 0.25 | 0.004 | 0.006 | 0.010 |
| A2   |       | 1.47  |      |       | 0.058 |       |
| b    | 0.31  | 0.2   |      | 0.012 | 0.008 |       |
| c    | 0.254 | 0.17  |      | 0.010 | 0.007 |       |
| D    | 8.56  | 8.66  | 8.76 | 0.337 | 0.341 | 0.345 |
| E    | 5.8   | 6     | 6.2  | 0.228 | 0.236 | 0.244 |
| E1   | 3.8   | 3.91  | 4.01 | 0.150 | 0.154 | 0.158 |
| e    |       | 0.635 |      |       | 0.025 |       |
| L    | 0.4   | 0.635 | 0.89 | 0.016 | 0.025 | 0.035 |
| h    | 0.25  | 0.33  | 0.41 | 0.010 | 0.013 | 0.016 |
| <    | 8°    | 0°    |      |       |       |       |

Figure 21. QSOP-24 package dimensions




Table 15. QSOP-24 tape and reel

| Dim. | mm.  |      |      | inch  |         |       |
|------|------|------|------|-------|---------|-------|
|      | Min  | Typ  | Max  | Min   | Typ     | Max   |
| R1   | 12.8 | 13   | 13.5 | 5.039 | 5.118   | 5.315 |
| R2   |      | 330  |      |       | 129.921 |       |
| R3   |      | 100  |      |       | 39.37   |       |
| eint |      | 16.4 |      |       | 6.457   |       |
| e1   | 1.5  | 2    | 2.5  | 0.591 | 0.787   | 0.984 |

Table 16. QSOP-24 tape and reel dimensions




Table 17. TSSOP24 mechanical data

| Dim. | mm.  |          |      | inch   |            |        |
|------|------|----------|------|--------|------------|--------|
|      | Min. | Typ.     | Max. | Min.   | Typ.       | Max.   |
| A    |      |          | 1.1  |        |            | 0.043  |
| A1   | 0.05 |          | 0.15 | 0.002  |            | 0.006  |
| A2   |      | 0.9      |      |        | 0.035      |        |
| b    | 0.19 |          | 0.30 | 0.0075 |            | 0.0118 |
| c    | 0.09 |          | 0.20 | 0.0035 |            | 0.0079 |
| D    | 7.7  |          | 7.9  | 0.303  |            | 0.311  |
| E    | 4.3  |          | 4.5  | 0.169  |            | 0.177  |
| e    |      | 0.65 BSC |      |        | 0.0256 BSC |        |
| H    | 6.25 |          | 6.5  | 0.246  |            | 0.256  |
| K    | 0°   |          | 8°   | 0°     |            | 8°     |
| L    | 0.50 |          | 0.70 | 0.020  |            | 0.028  |

Figure 22. TSSOP24 package dimensions




Table 18. Tape and reel TSSOP24

| Dim. | mm.  |      |      | inch  |      |        |
|------|------|------|------|-------|------|--------|
|      | Min. | Typ. | Max. | Min.  | Typ. | Max.   |
| A    |      |      | 330  |       |      | 12.992 |
| C    | 12.8 |      | 13.2 | 0.504 |      | 0.519  |
| D    | 20.2 |      |      | 0.795 |      |        |
| N    | 60   |      |      | 2.362 |      |        |
| T    |      |      | 22.4 |       |      | 0.882  |
| Ao   | 6.8  |      | 7    | 0.268 |      | 0.276  |
| Bo   | 8.2  |      | 8.4  | 0.323 |      | 0.331  |
| Ko   | 1.7  |      | 1.9  | 0.067 |      | 0.075  |
| Po   | 3.9  |      | 4.1  | 0.153 |      | 0.161  |
| P    | 11.9 |      | 12.1 | 0.468 |      | 0.476  |

Figure 23. Reel dimensions




Table 19. SO-24 mechanical data

| Dim. | mm.       |       |       | inch  |       |       |
|------|-----------|-------|-------|-------|-------|-------|
|      | Min.      | Typ.  | Max.  | Min.  | Typ.  | Max.  |
| A    |           |       | 2.65  |       |       | 0.104 |
| a1   | 0.1       |       | 0.2   | 0.004 |       | 0.008 |
| a2   |           |       | 2.45  |       |       | 0.096 |
| b    | 0.35      |       | 0.49  | 0.014 |       | 0.019 |
| b1   | 0.23      |       | 0.32  | 0.009 |       | 0.012 |
| C    |           | 0.5   |       |       | 0.020 |       |
| c1   | 45°(typ.) |       |       |       |       |       |
| D    | 15.20     |       | 15.60 | 0.598 |       | 0.614 |
| E    | 10.00     |       | 10.65 | 0.393 |       | 0.419 |
| e    |           | 1.27  |       |       | 0.050 |       |
| e3   |           | 13.97 |       |       | 0.550 |       |
| F    | 7.40      |       | 7.60  | 0.291 |       | 0.300 |
| L    | 0.50      |       | 1.27  | 0.020 |       | 0.050 |
| S    | °(max.) 8 |       |       |       |       |       |

Figure 24. SO-24 package dimensions




Table 20. Tape and reel SO-24

| Dim. | mm.  |      |      | inch  |      |        |
|------|------|------|------|-------|------|--------|
|      | Min. | Typ. | Max. | Min.  | Typ. | Max.   |
| A    |      |      | 330  |       |      | 12.992 |
| C    | 12.8 |      | 13.2 | 0.504 |      | 0.519  |
| D    | 20.2 |      |      | 0.795 |      |        |
| N    | 60   |      |      | 2.362 |      |        |
| T    |      |      | 30.4 |       |      | 1.197  |
| Ao   | 10.8 |      | 11.0 | 0.425 |      | 0.433  |
| Bo   | 15.7 |      | 15.9 | 0.618 |      | 0.626  |
| Ko   | 2.9  |      | 3.1  | 0.114 |      | 0.122  |
| Po   | 3.9  |      | 4.1  | 0.153 |      | 0.161  |
| P    | 11.9 |      | 12.1 | 0.468 |      | 0.476  |

Figure 25. Reel dimensions





Table 21. TSSOP24 exposed pad

| Dim. | mm   |      |      | inch  |        |        |
|------|------|------|------|-------|--------|--------|
|      | Min. | Typ. | Max. | Min.  | Typ.   | Max.   |
| A    |      |      | 1.2  |       |        | 0.047  |
| A1   |      |      | 0.15 |       | 0.004  | 0.006  |
| A2   | 0.8  | 1    | 1.05 | 0.031 | 0.039  | 0.041  |
| b    | 0.19 |      | 0.30 | 0.007 |        | 0.012  |
| c    | 0.09 |      | 0.20 | 0.004 |        | 0.0089 |
| D    | 7.7  | 7.8  | 7.9  | 0.303 | 0.307  | 0.311  |
| D1   | 4.7  | 5.0  | 5.3  | 0.185 | 0.197  | 0.209  |
| E    | 6.2  | 6.4  | 6.6  | 0.244 | 0.252  | 0.260  |
| E1   | 4.3  | 4.4  | 4.5  | 0.169 | 0.173  | 0.177  |
| E2   | 2.9  | 3.2  | 3.5  | 0.114 | 0.126  | 0.138  |
| e    |      | 0.65 |      |       | 0.0256 |        |
| K    | 0°   |      | 8°   | 0°    |        | 8°     |
| L    | 0.45 | 0.60 | 0.75 | 0.018 | 0.024  | 0.030  |

Figure 26. TSSOP24 dimensions



## 9 Revision history

**Table 22. Document revision history**

| Date        | Revision | Changes                                                                                                                                                                 |
|-------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 9-Jan-2007  | 1        | First release                                                                                                                                                           |
| 21-May-2007 | 2        | Updated <a href="#">Table 7 on page 6</a>                                                                                                                               |
| 10-Jul-2007 | 3        | Updated <a href="#">Table 9: Truth table on page 10</a>                                                                                                                 |
| 28-Feb-2008 | 4        | Updated <a href="#">Table 15: TSSOP24 exposed-pad on page 23</a><br>Added QSOP-24 package information <a href="#">Table 14</a> and <a href="#">Figure 21 on page 23</a> |
| 23-Oct-2009 | 5        | Updated <a href="#">Figure 7 on page 10</a> , <a href="#">Chapter 3 on page 6</a>                                                                                       |
| 20-Jan-2010 | 6        | Updated <a href="#">Table 5 on page 4</a>                                                                                                                               |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2010 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)