

Distributed by:



www.Jameco.com ♦ 1-800-831-4242

The content and copyrights of the attached
material are the property of its owner.

SUNON KDE Series

DC Brushless Fan

3028

:30x28x10mm



Model	P/N	Bearing	Rating Voltage (VDC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)	Weight (g)
KDE0528AFV1-8	MS	● VAPOR	5	0.18	0.9	11000	2.4	0.13	30	9
KDE0528AFV2-8	MS	● SLEEVE	5	0.12	0.6	9000	1.8	0.10	28	9
KDE0528AFB1-8		○ BALL	5	0.18	0.9	11000	2.4	0.13	32	9
KDE0528AFB2-8		○	5	0.12	0.6	9000	1.8	0.10	30	9
KDE0528AFB3-8		○	5	0.06	0.3	6500	1.5	0.08	27	9
KDE0528AFB1-8	MS	○	5	0.18	0.9	11000	2.4	0.13	31	9
KDE0528AFB2-8	MS	○	5	0.12	0.6	9000	1.8	0.10	29	9

3006

:30x30x6mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KDE0503PEV1-8	MS.N	●	5	0.18	0.9	9500	4.9	0.14	28	6
KDE0503PEV2-8	MS.N	●	5	0.11	0.55	8000	3.7	0.09	23	6
KDE0503PEB1-8		○	5	0.13	0.65	9500	3.0	0.15	31	6
KDE0503PEB2-8		○	5	0.09	0.45	7500	2.4	0.08	26	6
KDE0503PEB3-8		○	5	0.05	0.3	5500	1.9	0.065	20	6
KDE0503PEB1-8	MS.N	○	5	0.18	0.9	9500	4.9	0.14	29	6
KDE0503PEB2-8	MS.N	○	5	0.11	0.55	8000	3.7	0.09	24	6

3010

:30x30x10mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KDE0503PFV1-8	MS	●	5	0.18	0.9	8000	5.1	0.14	22.5	7.5
KDE0503PFV2-8	MS	●	5	0.12	0.6	7000	4.2	0.11	20.5	7.5
KDE0503PFV3-8	MS	●	5	0.06	0.3	5000	3.15	0.06	18.5	7.5
KDE0503PFV4-8	MS	●	5	0.03	0.15	4000	2.59	0.04	17.5	7.5
KDE0503PFB1-8		○	5	0.18	0.9	9500	3.5	0.14	27	7.5
KDE0503PFB2-8		○	5	0.12	0.6	8000	3.0	0.11	25	7.5
KDE0503PFB3-8		○	5	0.06	0.3	5500	2.3	0.07	18.5	7.5
KDE0503PFB4-8		○	5	0.03	0.15	4000	1.4	0.03	18	7.5
KDE0503PFB1-8	MS	○	5	0.18	0.9	8000	5.1	0.14	24	7.5
KDE0503PFB2-8	MS	○	5	0.12	0.6	7000	4.2	0.11	22	7.5
KDE0503PFB3-8	MS	○	5	0.06	0.3	5000	3.15	0.06	20	7.5
KDE0503PFB4-8	MS	○	5	0.03	0.15	4000	2.59	0.04	18	7.5
KDE0503PFB1-8	V	○	5	0.18	0.9	8000	5.1	0.14	28	7.5
KDE0503PFB2-8	V	○	5	0.12	0.6	7000	4.2	0.105	26	7.5
KDE0503PFB3-8	V	○	5	0.06	0.3	5000	3.15	0.06	24	7.5
KDE0503PAB1-8	V	○	5	0.18	0.9	8000	5.1	0.14	28	7.5
KDE0503PAB2-8	V	○	5	0.12	0.6	7000	4.2	0.105	26	7.5
KDE0503PAB3-8	V	○	5	0.06	0.3	5000	3.15	0.06	24	7.5
KDE1203PFB1-8		○	12	0.08	0.9	9500	3.5	0.14	27	9.5
KDE1203PFB2-8		○	12	0.07	0.8	8000	3.0	0.11	25	9.5
KDE1203PFB3-8		○	12	0.05	0.6	6500	2.3	0.07	18.5	9.5
KDE1203PFB1-8	V	○	12	0.08	0.9	8000	5.1	0.14	32	7.5
KDE1203PFB2-8	V	○	12	0.07	0.8	7000	4.2	0.11	20.5	7.5
KDE1203PFB3-8	V	○	12	0.05	0.6	5000	3.15	0.06	25	7.5

3015

:30x30x15mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KDE0503PHB1-8		○	5	0.17	0.9	8500	6.0	0.16	27	12
KDE0503PHB2-8		○	5	0.12	0.6	7000	4.8	0.11	22	12
KDE0503PHB3-8		○	5	0.07	0.35	5500	3.2	0.10	17	12