



■ 80x80x25



Model	Bearing ● VAPO	Rating Voltage (VDC)	Power Current (mA)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)	Weight (g)
PF80251V1-0000-A99	●	12	341	4.10	4800	60	0.41	46.5	91.0
PF80251V2-0000-A99	●	12	285	3.40	4500	57	0.35	45.0	91.0
PF80251V3-0000-A99	●	12	223	2.70	4200	53	0.30	43.5	91.0



Model	Bearing ⊙ 2BALL	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
PF80251B1-0000-A99	⊙	12	341	4.10	4800	60	0.41	47.5	91.0
PF80251B2-0000-A99	⊙	12	285	3.40	4500	57	0.35	46.0	91.0
PF80251B3-0000-A99	⊙	12	223	2.70	4200	53	0.30	44.5	91.0



Model	Bearing ● VAPO	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
ME80251VX-0000-A99	●	12	160	1.90	3600	45	0.23	37.0	89.0
ME80251V1-0000-A99	●	12	145	1.70	3200	41	0.18	33.0	77.0
ME80251V2-0000-A99	●	12	120	1.40	2900	37	0.15	30.0	75.0
ME80251V3-0000-A99	●	12	81	1.10	2600	33	0.11	28.0	75.0
ME80252VX-0000-A99	●	24	90	2.20	3600	45	0.23	37.0	89.0
ME80252V1-0000-A99	●	24	73	1.80	3200	41	0.18	33.0	75.0
ME80252V2-0000-A99	●	24	59	1.40	2900	37	0.15	30.0	75.0
ME80252V3-0000-A99	●	24	49	1.20	2600	33	0.11	28.0	75.0

Model	Bearing ⊙ 2BALL	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
EE80251BX-0000-A99	⊙	12	150	1.80	3600	45	0.23	38	89.0
EE80251B1-0000-A99	⊙	12	145	1.70	3200	41	0.18	33	75.0
EE80251B2-0000-999	⊙	12	120	1.40	2900	37	0.15	30	75.0
EE80251B3-0000-999	⊙	12	90	1.10	2600	33	0.11	28	75.0
EE80252BX-0000-A99	⊙	24	80	1.92	3600	45	0.23	38	89.0
EE80252B1-0000-A99	⊙	24	73	1.80	3200	41	0.18	33	75.0
EE80252B2-0000-999	⊙	24	64	1.50	2900	37	0.15	30	75.0
EE80252B3-0000-999	⊙	24	50	1.20	2600	33	0.11	28	75.0



Model	Bearing ○ SLEEVE	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
EE80251S1-0000-A99	○	12	145	1.7	3200	41	0.18	33	75.0
EE80251S2-0000-A99	○	12	120	1.4	2900	37	0.15	30	75.0
EE80251S3-0000-A99	○	12	90	1.1	2600	33	0.11	28	75.0
EE80252S1-0000-A99	○	24	73	1.8	3200	41	0.18	33	75.0
EE80252S2-0000-A99	○	24	64	1.5	2900	37	0.15	30	75.0
EE80252S3-0000-A99	○	24	52	1.3	2600	33	0.11	28	75

* If you need special specification. Please contact Sunon sales.

* Specifications are subject to change without notice. Specifications in this catalog are for reference. More Sunon products information please visit SUNON web site at <http://www.sunon.com>.