

Switchcraft®**conxall®**[Home](#) [About Us](#) [Products](#) [Applications](#) [Sales Support](#) [Contact Us](#) Search [Industrial Products](#) > [Jacks and Plugs](#) > [DC Power Jack and Plug Series](#) > [DC Power Jacks](#) > [Straight DC Power Jacks](#)

Straight DC Power Jacks



Straight versions of our DC power jacks. These versions have threaded bushings to allow use of both standard and locking power plugs. The L versions of the power jacks have a longer bushing (0.319") to accommodate thicker panel mount applications. Available in pin diameters of 0.050", 0.080", and 0.100".

[enlarge](#)[Products](#)[Specifications](#)[User Guide](#)

Need more info? Contact Switchcraft customer service

[Printer friendly version](#)

MATERIALS:

Housing: Thermoplastic**Bushing:** Plated copper alloy**Terminals:** Plated copper alloy**Insulators:** Rigid Plastic**Hardware:** Supplied with one P2439 nickel plated copper alloy hex nut, and one P2441 nickel plated steel flat washer

ELECTRICAL:

Current Rating: 5A, 12V DC resistive**Contact Resistance:** 0.01 Ohms max. (initial),
0.02 Ohms max. (after humidity, durability exposure),
0.10 Ohms max. (after salt spray)**Insulation Resistance:** 10,000 Mohms min. (initial),
1,000 Mohms min. (after humidity, durability exposure)**Dielectric Withstanding Voltage:** 500 VAC max.

MECHANICAL:

Lifecycles: 10,000 cycles min.

5555 N Elston Ave • Chicago • Illinois • 60630 • USA • 1.773.792.2700

[Home](#) [About Us](#) [Sales](#) [Contact Us](#) [Login](#)**Switchcraft®**
KOREA**Switchcraft®**
USA**conxall®**