





3 PIN




4 PIN



5 PIN



6 PIN



7 PIN

CONTACTS AS VIEWED FACING FEMALE CONECTOR

AAA F Z

SERIES: **Q-G° CONNECTOR**

OF CONTACT SOCKETS: **3, 4, 5, 6 OR 7**




GENDER: **FEMALE**

HANDLE STYLE: **BLANK** - METAL HANDLE (SEE FINISH BELOW)
P - PLASTIC HANDLE, BLACK

FINISH: **BLANK** - NICKEL HANDLE & CONNECTOR, WITH BLACK FLEX RELIEF & GREEN INSERT
B - BLACK HANDLE & CONNECTOR, WITH BLACK FLEX RELIEF & BLACK INSERT
W - WHITE HANDLE & NICKEL FINISH CONNECTOR WITH WHITE FLEX RELIEF & GREEN INSERT G

CONTACT SOCKET PLATING: **BLANK** - SILVER
AU - GOLD

FLEX RELIEF STYLE: **BLANK** - FLEX RELIEF I.D. 0.135 [3.4mm]
RECOMMENDED CABLE O.D. 0.100 - 0.220 [2.5mm - 5.6mm]
L - FLEX RELIEF I.D. 0.225 [5.7mm]
RECOMMENDED CABLE O.D. 0.220 - 0.285 [5.6mm - 7.2mm] F



CUSTOMER DRAWING

NOTES:

1. CONNECTORS AND HANDLES ARE SHIPPED SIDE BY SIDE OR IN BULK.
2. MATERIALS:
F HANDLE METAL - ZINC ALLOY, NICKEL PLATED OR BLACK OR WHITE PAINTED
HANDLE PLASTIC - THERMOPLASTIC, BLACK
CABLE CLAMP - THERMOPLASTIC, BLACK
FLEX RELIEF - THERMOPLASTIC, BLACK OR WHITE
HOUSING AND LATCH - ZINC ALLOY, NICKEL OR BLACK SATIN CHROME PLATED
INSULATOR - THERMOPLASTIC, GREEN OR BLACK
GROUND TERMINAL - SPECIAL COPPER ALLOY, TIN PLATED
CONTACT SOCKETS - SPECIAL COPPER ALLOY, SILVER OR GOLD PLATED
O-RING - THERMOPLASTIC RUBBER, BLACK
3. THESE PRODUCTS ARE RoHS COMPLIANT.

G	27473	03/27/15	PC	TJK	☆ STAR SYMBOL DENOTES CRITICAL DIMENSION	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.											
F	27081	01/25/13	BL	TJK		UNLESS OTHERWISE SPECIFIED	SIZE		WIDTH		MULT		LBS/M		TEMPER		
E	25891	9-9-08	SRC	TJK	1. ALL DIMENSIONS IN INCHES - TWO PLACE DECIMALS ±0.01 - THREE PLACE DECIMALS ±0.005 - ANGLES ±1° - ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R. 2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002 3. REMOVE ALL BURRS	FINISH					MATERIAL						
D	25711	10-17-07	JGK	TJK		SPEC No.					SPEC No.						
C	24940	3-11-05	JL	TJK		FIRST USED ON				SCALE 1.5:1			Switchcraft®				
B	24552	10-13-03	JL	BRH		DATE DRAWN 03-07-03	BY BRH	CHKD BRH 8-12-03		APVD BRH 8-12-03							
A	24446	8-12-03	JL	BRH		SHEET 1 OF 1											
REV	ECO NUMBER	DATE	BY	APVD	DO NOT SCALE DRAWING	NAME FEMALE XLR CONNECTOR, RoHS					PART No. AAA_FZ SERIES				REV G		
REVISIONS																	