



## Product Information

# Envi-Ro-Tech™ 1747 Anti-Static Freezer

Anti-Static Freezer  
1747

## Introduction

---

A rapidly evaporating HFC-134a product that contains an anti-static agent. This product is used as a troubleshooting aid in static sensitive areas for intermittently faulting capacitors, resistors, semi-conductors and other defective components.

### Features / Benefits

Non-Flammable  
Non-Ozone Depleting  
Anti-Static Agent  
Chills to -40°F  
Zero Residue

## Chemical Components

---

|                                |            |     |
|--------------------------------|------------|-----|
| 1,1,1,2-Tetrafluoroethane..... | (811-97-2) | 98% |
| Methanol.....                  | (67-56-1)  | 2%  |

## Environmental Policy

---

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

## Packaging and Availability

---

Envi-Ro-Tech™ 1747 Anti-Static Freezer is available in the following sizes:

1747-10S                      10 Ounce Aerosol

## Resources

---

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

**North America**

Tech Spray L.P.  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

**Europe**

Techspray International  
UNIT 4, 44/46 Bunyan Road, Kempston  
Bedford MK42 8HL United Kingdom  
+44 (0) 1234 855443  
email: [tseurope@techspray.com](mailto:tseurope@techspray.com)

**Countries Outside US**

Call to locate a distributor  
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.  
P.O. Box 949  
Amarillo, TX 79105  
[www.techspray.com](http://www.techspray.com)

[English MSDS](#)  
[French MSDS](#)  
[German MSDS](#)  
[Italian MSDS](#)  
[Spanish MSDS](#)

