

CGB-38-78010M Product Details



CGB-38-78010M

Time Delay Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- CG Series
- Input Voltage = 120 VAC
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 30 VDC or 277 VAC
- Mounting Options = Socket

TE Internal Number: 8-1393136-1



Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • CG CMOS IC Time Delay Relay (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Schematic • Wiring Diagram <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Series = CG • Termination Type = 11-Pin Octal Style Plug <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Mounting Options = Socket <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Input Voltage (VAC) = 120 • Contact Rating = 10A @ 30 VDC or 277 VAC <p>Dimensions:</p> <ul style="list-style-type: none"> • Approx. Dimensions (L x W x H) (mm [in]) = 61.10 x 45.20 x 74.60 [2.407 x 1.780 x 2.939] <p>Body Features:</p> <ul style="list-style-type: none"> • Enclosure Type = Yellow Plastic Case <p>Contact Features:</p> <ul style="list-style-type: none"> • Delay Time = 1 minute to 10 minutes • Type of Control = Knob • Repeatability, Max. = $\pm 0.5\%$ (AC) • Contact Base Material = Silver Cadmium Oxide 	<p>Configuration Features:</p> <ul style="list-style-type: none"> • Contact - Arrangement = 2 Form C, DPDT, 2 C/O • Multiple Timing Ranges = Without <p>Industry Standards:</p> <ul style="list-style-type: none"> • Approved Standards = CSA Certified, UL Recognized • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not relevant for lead free process <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Temperature Range (°C) = -10 - +55 <p>Operation/Application:</p> <ul style="list-style-type: none"> • Mode of Operation = Delay on Release <p>Other:</p> <ul style="list-style-type: none"> • Brand = Potter & Brumfield