



MICROSMD035F-2 Product Details



MICROSMD035F-2

TE Internal Number: RF1352-000



Active

PolySwitch Resettable Devices

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Surface Mount Application
- Vmax = 6 V
- Imax = 40 A
- Family Name = microSMD
-

• None Available Catalog Pages/Data Sheets: • CP CATALOG 2011 - SURFACE-MOUNT (PDF, English) Product Specifications: • microSMD035F (PDF, English) Application Specifications: • None Available Instruction Sheets: • None Available CAD Files: • None Available	Related Products: • Tooling

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: • Family Name = microSMD • UL File Number = E74889 • CSA File Number = CA78165 Electrical Characteristics: • Vmax (V) = 6 • Imax (A) = 40 • IH (Room Temperature) (A) = 0.35 • IT (Room Temperature) (A) = 0.75 • Rmin (Ω) = 0.32 • R1 Max [Post Trip] (Ω) = 1.30 Termination Features: • Construction = Surface Mount Configuration Features: • Form Factor (inches) = 1210 • Form Factor (mm) = 3225	Industry Standards: • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C • RoHS/ELV Compliance History = Always was RoHS compliant • TUV Certificate No. = R72111045 Environmental: • Operating Temperature (Max.) (°C) = 85 Operation/Application: • Application = Surface Mount Packaging Features: • Packaging Method = Tape & Reel Other: • Brand = Raychem