




W31-X2M1G-5 Product Details



W31-X2M1G-5

TE Internal Number: 4-1393247-2
 Active

Thermal Circuit Breakers

Converted to EU RoHS but not ELV Compliant
(Statement of Compliance)

Product Highlights:

- Circuit Breaker
- W31 Series
- 1 Poles
- Actuator Style = Toggle
- Current Rating = 5 A

Documentation & Additional Information	
Product Drawings: • None Available Catalog Pages/Data Sheets: • W23/31 Toggle or Pusl/Pull Actuator Thermal Circuit ... (PDF, English) Product Specifications: • None Available Application Specifications: • None Available Instruction Sheets: • None Available CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version 0905) • 3D Model (IGES, Version 0905) • 3D Model (STEP, Version 0905)	Additional Information: • Product Line Information Additional Product Images: • Schematic • Panel Cutout • Mounting Hardware Related Products: • Tooling
Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: • Product Type = Circuit Breaker • Series = W31 • Actuator Style = Toggle • Termination Type = 8-32 Screws 90° to Each Other (Screws and Washers Installed) Mechanical Attachment: • Mounting Options = Two Hex Nuts/Lockwasher • Mounting Bushing = 15/32"-32 Threaded Bushing .320" Long Double "D", Silver Color Electrical Characteristics: • Current Rating (A) = 5 • Operating Voltage, Max. = 50 VDC, 250 VAC • Interrupt Capacity = 2,000 A @ 50 VDC or 1,000 A @ 240 VAC	Contact Features: • Number of Poles = 1 • Trip Time at 200% = 6 to 22 Seconds • Toggle Color = Silver Metal, Round with Amp Rate Marking Configuration Features: • Circuit Function = Series Trip Industry Standards: • RoHS/ELV Compliance = RoHS/Not ELV Compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives • Approved Standards = UL Recognized, CSA Certified Other: • Brand = Potter & Brumfield