




## V23101D 5A201 Product Details



V23101D 5A201  
(1-1393779-1)  
TE Internal Number: 1-1393779-1  
Active

[View 3D PDF](#)

### Communications/Signal PC Board Relays

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- W11/V23101 Series
- Contact - Current Class = 0A to 2A Class
- Contact - Rated Current = 1.25 A
- Terminal Type = PCB-THT
- Contact - Arrangement = 1 Form C (CO)

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- [W11 Relay Datasheet \(PDF, English\)](#)

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version S00C\)](#)
- [3D Model \(IGES, Version S00C\)](#)
- [3D Model \(STEP, Version S00C\)](#)

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Electrical Characteristics:

- Contact - Current Class = 0A to 2A Class
- Contact - Rated Current (A) = 1.25
- Contact - Limiting Continuous Current (A) = 1.25
- Contact - Limiting Making Current (A) = 1.25
- Contact - Limiting Breaking Current (A) = 1.25
- Insulation - Initial Dielectric Between Coil/Contact Class = 500V to 1000V Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 750
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 1000
- Contact - Rated Voltage (VAC) = 125
- Contact - Rated Voltage (VDC) = 120
- Contact - Switching Voltage Max. (VAC) = 125
- Contact - Switching Voltage Max. (VDC) = 120
- Contact - Limiting Short-Time Current (A) = 1.25
- Coil - Rated Voltage (VDC) = 9
- Coil - Resistance ( $\Omega$ ) = 180
- Coil - Rated Power, DC (mW) = 450
- Coil - Rated Power Class = 400mW to 500mW Class
- Insulation - Initial Insulation Resistance (M $\Omega$ ) = 1000000
- Contact - Switching Recommended Load, Min. = 10mA at 0.02V

#### Dimensions:

- Mechanical - Length Class = 14mm to 16mm Class
- Length (mm[in]) = 15.49 [0.610]
- Mechanical - Width Class = 10mm to 12mm Class
- Width (mm[in]) = 10.50 [0.413]
- Mechanical - Height Class = 11mm to 12mm Class
- Height (mm[in]) = 11.50 [0.453]

#### Body Features:

- Weight (g [oz]) = 4.00 [0.141]
- Mount Type = PCB

#### Contact Features:

- Terminal Type = PCB-THT
- Contact Material = AgPd, gold plated
- Contact - Number of Poles = 1

#### Configuration Features:

- Contact - Arrangement = 1 Form C (CO)
- Coil - Magnetic System = Monostable, DC

#### Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive
- Approved/Registered Standards = cULus

#### Environmental:

- Environmental - Category of Protection = RTIII
- Environmental - Ambient Temperature, Max. ( $^{\circ}$ C [ $^{\circ}$ F]) = 85 [185]
- Environmental - Ambient Temperature Class = 70°C to 85°C Class

#### Packaging Features:

- Packaging Method = Tube

#### Other:

- Series = W11/V23101
- Brand = Axicom

### Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)

### Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

### Keep Me Informed

