

## 1825080-5 Product Details

[Share](#) [Print](#) [Email](#)


**1825080-5**  
(SLS260PC04)

TE Internal Number: 1825080-5

 **Active**

 [View 3D PDF](#)

### Slide Switches

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- 6 Positions
- Double Pole - Six Throw Configuration (Pole-Throw)
- Actuator Style = Top
- Actuator Color = Black
- SLS Series

[View all Features](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [SEE 2 TO 6 POSITION](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- [SWITCHES CORE PROGRAM CATALOG](#) (PDF, English)

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version B)
- [3D Model](#) (IGES, Version B)
- [3D Model](#) (STEP, Version B)

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Configuration (Pole-Throw) = Double Pole - Six Throw
- Actuator Style = Top
- Series = SLS
- Mount Angle = Vertical
- Terminal Configuration = Standard
- Grade = Economy
- Termination Type = PC

#### Electrical Characteristics:

- Contact Rating = 150mA @ 12 VDC, 250mA @ 125 VAC

#### Body Features:

- [Number of Positions](#) = 6
- Actuator Color = Black
- Mount Style = Through-Hole
- PCB Tail Length (mm [in]) = 2.79 [0.110]
- Actuator Length (mm [in]) = 5.00 [0.197]
- Actuator Material = PBT
- Actuator Travel = 3.20 [.126]

#### Contact Features:

- Contact Plating = Silver
- Contact Base Material = Copper Alloy

#### Housing Features:

- UL Flammability Rating = UL 94-HB

#### Configuration Features:

- Number of Actuators = Single

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Identification Marking:

- Stamped Marking = With

#### Other:

- Brand = Tyco Electronics

### Corporate Information

[Who We Are](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)

### Quick Links

[Check Distributor Inventory](#)  
[Cross Reference](#)  
[Find Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

### Customer Support

[Email or Chat With Us](#)  
[Find a Phone Number](#)  
[Search Knowledge Base](#)  
[Manage your Account](#)

### Keep Me Informed

Receive TE News, Events & Technology Updates

[➤](#)

